


3 and 4-Wire M12 *euromast*® Cordsets, "L" Style Compact Plug Body

- Straight Male Connector
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection
- 250 V, 4 A



Housing Style	Part Number	Cable	Features	Pinout
	RSL 4-*	AWM PVC Grey 3x20 AWG 105°C 5.2 mm OD Cable #RF50528-*M†	<i>flexlife</i> ®	1. BN 2. N/C 3. BU 4. BK
	RSL 4-*/S90	AWM PUR Grey 3x22 AWG 105°C 5.2 mm OD Cable #RF50518-*M†	<i>Cut/Abrasion Immune</i>	
	RSL 4.4-*	AWM PVC Grey 4x22 AWG 105°C 5.2 mm OD Cable #RF50516-*M†	<i>flexlife</i>	
	RSL 4.4-*/S90	AWM PUR Grey 4x22 AWG 105°C 5.2 mm OD Cable #RF50532-*M†	<i>Cut/Abrasion Immune</i>	1. BN 2. WH 3. BU 4. BK
	RSL 4.4-*/S715	AWM PVC Yellow 4x22 AWG 105°C 5.2 mm OD Cable #RF50530-*M†	<i>flexlife</i>	

Cordsets



* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.
 ** Standard coupling nut material is nickel plated brass "RSL ..".
 † See Section N for *reelfast*® cable information.