





3 and 4-Wire M12 *euromast*® Cordsets with and without LEDs, Rubber

- Right Angle Female Connectors
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection
- 10-30 VDC, 4 A



Housing Style	Part Number	Cable	Features	Pinout
 <p>WKE ..**</p>	WKE 4T-* -P7X2/S600	SJOOW CPE Yellow 3x18 AWG 105°C 8.5 mm OD Cable #RF50644-*M [†]	PNP Signal, Weld Flash Immune, Flame Immune	 <ol style="list-style-type: none"> 1. BN 2. N/C 3. BU 4. BK
	WKE 4T-* -N7X2/S600	SJOOW CPE Yellow 3x18 AWG 105°C 8.0 mm OD Cable #RF50654-*M [†]	NPN Signal, Weld Flash Immune, Flame Immune	
 <p>WKE 4.4T-**-**</p>	WKE 4.4T-2-P7X3/S600	SJOOW CPE Yellow 4x18 AWG 105°C 8.5 mm OD Cable #RF50644-*M [†]	PNP Signal, Weld Flash Immune, Flame Immune	 <ol style="list-style-type: none"> 1. BN 2. WH 3. BU 4. BK

Cordsets

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.
 ** Standard coupling nut material is nickel plated brass.
 † See Section N for *reelfast*® cable information.
 See page D88 for LED diagrams.