

4-Wire M12 *eurofast*® Cordsets, "C" Style Medium Plug Body

- Right Angle Female Connector
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection
- 250 V, 4 A



Housing Style	Part Number	Cable	Features	Pinout
<p>WKC ..**</p> <p>1.736 [44.1] 1.122 [28.5] ø.532 [13.5] M12x1</p> <p>WKCV ..**</p> <p>1.736 [44.1] 1.122 [28.5] ø.591 [15.0] M12x1</p>	WKC 4.4T-*	AWM PVC Yellow 4x18 AWG 105°C 7.3 mm OD Cable #RF50579-*M [†]	<i>flexlife</i> ®	<p>1. BN 2. WH 3. BU 4. BK</p>
	WKC 4.4T-*/S90	AWM PUR Yellow 4x18 AWG 105°C 7.3 mm OD Cable #RF50544-*M [†]	Cut/Abrasion Immune	
	WKC 4.4T-*/S622	AWM PVC Grey 4x18 AWG 105°C 7.3 mm OD Cable #RF50580-*M [†]	<i>flexlife</i>	
	WKC 4.4T-*/S824	PLTC PVC Grey 4x18 AWG 105°C 7.2 mm OD Cable #RF50844-*M [†]	Tray Rated	
	WKC 4.4T-*/S1587	AWM TPE Yellow 4x18 AWG 105°C 7.3 mm OD Cable #RF50956-*M [†]	Weld Flash Immune	
	WKC 4.4T-*/S101/S849	AWM TPE Grey 4x22 AWG 105°C 5.7 mm OD Cable #RF50941-*M [†]	<i>flexLife-10, High Flex Over 10 Million Cycles</i>	
	WKC 4.4T-*/S101	AWM TPE Yellow 4x18 AWG 105°C 7.2 mm OD Cable #RF50968-*M [†]		
	WKC 4.4T-*/S1062	AWM PVC Yellow 4x18 AWG 105°C 7.3 mm OD Cable #RF50579-*M [†]	<i>flexlife</i> ® Cable, PVC plug body with PVC contact carriers	

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "WKC .."; "WKCV .." indicates 316 stainless steel.

† See Section N for *reelfast*® cable information.