

4-Wire M12 *eurofast*® Cordsets, "C" Style Medium Plug Body

- Right Angle Male Connector
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection
- 250 V, 4 A



Housing Style	Part Number	Cable	Features	Pinout
	WSC 4.4T-*	AWM PVC Yellow 4x18 AWG 105°C 7.3 mm OD Cable #RF50579- [†] M [†]	<i>flexlife</i> ®	
	WSC 4.4T-*/S90	AWM PUR Yellow 4x18 AWG 105°C 7.3 mm OD Cable #RF50544- [†] M [†]	<i>Cut/Abrasion Immune</i>	
	WSC 4.4T-*/S622	AWM PVC Grey 4x18 AWG 105°C 7.3 mm OD Cable #RF50580- [†] M [†]	<i>flexlife</i>	
	WSC 4.4T-*/S824	PLTC PVC Grey 4x18 AWG 105°C 7.2 mm OD Cable #RF50844- [†] M [†]	<i>Tray Rated</i>	
	WSC 4.4T-*/S1587	AWM TPE Yellow 4x18 AWG 105°C 7.3 mm OD Cable #RF50956- [†] M [†]	<i>Weld Flash Immune</i>	
	WSC 4.4T-*/S101/S849	AWM TPE Grey 4x22 AWG 105°C 5.7 mm OD Cable #RF50941- [†] M [†]	<i>flexLife-10, High Flex Over 10 Million Cycles</i>	
	WSC 4.4T-*/S101	AWM TPE Yellow 4x18 AWG 105°C 7.2 mm OD Cable #RF50968- [†] M [†]		
	WSC 4.4T-*/S1062	AWM PVC Yellow 4x18 AWG 105°C 7.3 mm OD Cable #RF50579- [†] M [†]	<i>flexlife</i> ® Cable, PVC plug body with PVC contact carriers	

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "WSC .."; "WSCV .." indicates 316 stainless steel.

† See Section N for *reelfast*® cable information.