

4-Wire M12 eurofast® Cordsets, "C" Style Medium Plug Body

- Straight Male Connector
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection
- 250 V, 4 A



| Housing Style | Part Number          | Cable  | Features  | Pinout |
|---------------|----------------------|--|---|--------|
|               | RSC 4.4T-*           | AWM PVC Yellow<br>4x18 AWG<br>105°C<br>7.3 mm OD<br>Cable #RF50579-*M† | flexlife®   |        |
|               | RSC 4.4T-*/S90       | AWM PUR Yellow<br>4x18 AWG<br>105°C<br>7.3 mm OD<br>Cable #RF50544-*M† | Cut/Abrasion Immune   |        |
|               | RSC 4.4T-*/S622      | AWM PVC Grey<br>4x18 AWG<br>105°C<br>7.3 mm OD<br>Cable #RF50580-*M†   | flexlife  |        |
|               | RSC 4.4T-*/S824      | PLTC PVC Grey<br>4x18 AWG<br>105°C<br>7.2 mm OD<br>Cable #RF50844-*M†  | Tray Rated  |        |
|               | RSC 4.4T-*/S1587     | AWM TPE Yellow<br>4x18 AWG<br>105°C<br>7.3 mm OD<br>Cable #RF50956-*M† | weldlife,<br>Weld Flash Immune                              |        |
|               | RSC 4.4T-*/S101/S849 | AWM TPE Grey<br>4x22 AWG<br>105°C<br>5.7 mm OD<br>Cable #RF50941-*M†   | flexLife-10,<br>High Flex Over 10 Million                   |        |
|               | RSC 4.4T-*/S101      | AWM TPE Yellow<br>4x18 AWG<br>105°C<br>7.2 mm OD<br>Cable #RF50968-*M† |   |        |
|               | RSC 4.4T-*/S1062     | AWM PVC Yellow<br>4x18 AWG<br>105°C<br>7.3 mm OD<br>Cable #RF50579-*M† | flexlife® Cable,<br>PVC plug body with PVC contact carriers |        |

Cordsets

\* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.  
 \*\* Standard coupling nut material is nickel plated brass "RSC .."; "RSCV .." indicates 316 stainless steel.  
 † See Section N for reelfast® cable information.