

5-Wire M12 eurofast® Cordsets, "C" Style Medium Plug Body

- Right Angle Male Connector
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection
- 250 V, 4 A



Housing Style	Part Number	Cable	Features	Pinout
	WSC 4.5T-*/S653	PLTC PVC Grey 4x22 AWG 105°C Foil/Drain 5.2 mm OD Cable #RF50773-*M†	RFI/EMI Shielding Tray Rated	1. BN 2. WH 3. BU 4. BK 5. Drain
	WSC 4.5T-*/S1538	AWM PVC Grey 5x18 AWG 105°C 7.3 mm OD Cable #RF50630-*M†	flexlife®, green/yellow ground	1. BN 2. WH 3. BU 4. BK 5. GN/YE
	WSC 4.5T-*/S715/S849	AWM PVC Yellow 5x22 AWG 105°C 5.7 mm OD Cable #RF50684-*M†	flexlife, 22 AWG	1. BN 2. WH 3. BU 4. BK 5. GY
	WSC 4.5T-*/CS10288	AWM PVC Yellow 5x18 AWG 105°C 7.3 mm OD Cable #RF50549-*M†	flexlife, Green/Yellow Ground	1. BN 2. WH 3. BU 4. BK 5. GN/YE
	WSC 4.5T-*/S1062	AWM PVC Grey 5x22 AWG 105°C 5.7 mm OD Cable #RF50543-*M†	flexlife® Cable, PVC plug body with PVC contact carriers	
	WSC 4.5T-*/S1587	AWM TPE Yellow 5x18 AWG 80°C 6.4 mm OD Cable #RF51232-*M†	weldlife, Weld Flash Immune	
	WSC 4.5T-*/S1587/S771		Weld Flash Immune, Black Plug Body	
	WSCN 5T-*	PLTC PVC NAMUR Blue 5x22 AWG 105°C 6.8 mm OD Cable #RF50767-*M†	flexlife, 22 AWG, for VBN 40-H1141 multiBox	1. GN 2. WH 3. OG 4. BK 5. RD

Cordsets

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.
 ** Standard coupling nut material is nickel plated brass "WSC .."; "WSCV .." indicates 316 stainless steel.
 † See Section N for **reelfast**® cable information.