

5-Wire M12 *eurofast*® Cordsets, "C" Style Medium Plug Body

- Straight Male Connector
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection
- 250 V, 4 A



Housing Style	Part Number	Cable	Features	Pinout
<p>RSC ..**</p>	RSC 4.5T-*/S653	PLTC PVC Grey 4x22 AWG 105°C Foil/Drain 5.2 mm OD Cable #RF50773-*M†	<i>RFI/EMI Shielding</i> <i>Tray Rated</i>	1. BN 2. WH 3. BU 4. BK 5. Drain
	RSC 4.5T-*/S1538	AWM PVC Grey 5x18 AWG 105°C 7.3 mm OD Cable #RF50630-*M†	<i>flexlife</i> ®, <i>Green/Yellow Ground</i>	1. BN 2. WH 3. BU 4. BK 5. GN/YE
	RSC 4.5T-*/S715/S849	AWM PVC Yellow 5x22 AWG 105°C 5.7 mm OD Cable #RF50684-*M†	<i>flexlife</i> , 22 AWG	1. BN 2. WH 3. BU 4. BK 5. GY
	RSC 4.5T-*/CS10288	AWM PVC Yellow 5x18 AWG 105°C 7.3 mm OD Cable #RF50549-*M†	<i>flexlife</i> <i>Over 2 Million Cycles,</i> <i>Green/Yellow Ground</i>	1. BN 2. WH 3. BU 4. BK 5. GN/YE
	RSC 4.5T-*/S1062	AWM PVC Grey 5x22 AWG 105°C 5.7 mm OD Cable #RF50543-*M†	<i>flexlife</i> ® Cable, <i>PVC plug body with PVC contact carriers</i>	
	RSC 4.5T-*/S1587	AWM TPE Yellow 5x18 AWG 80°C 6.4 mm OD Cable #RF51232-*M†	<i>weldlife</i> , <i>Weld Flash Immune</i>	
	RSC 4.5T-*/S1587/S771		<i>Weld Flash Immune, Black Plug Body</i>	
	RSCN 5T-*	PLTC PVC NAMUR Blue 5x22 AWG 105°C 6.8 mm OD Cable #RF50767-*M†	<i>flexlife</i> , 22 AWG <i>Over 2 Million Cycles, for VBN 40-H1141 MultiBox</i>	1. GN 2. WH 3. OG 4. BK 5. RD

\* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

\*\* Standard coupling nut material is nickel plated brass "RSC .."; "RSCV .." indicates 316 stainless steel.

† See Section N for *reelfast*® cable information.