

6-Wire M12 eurofast® Cordsets, "C" Style Medium Plug Body

- Right Angle Female Connector
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection
- 60 VAC/75 VDC, 2 A



Housing Style	Part Number	Cable	Features	Pinout
	WKC 6T-*	AWM PVC Grey 6x24 AWG 105°C 5.7 mm OD Cable #RF50608- <sup>†</sup> M <sup>†</sup>	<i>flexlife</i> ®	
	WKC 6T-*/S90	AWM PUR Grey 6x24 AWG 105°C 5.7 mm OD Cable #RF50646- <sup>†</sup> M <sup>†</sup>	<i>Cut/Abrasion Immune</i>	
	WKC 6T-*/S101	AWM TPE Grey 6x24 AWG 105°C 5.7 mm OD Cable #RF50910- <sup>†</sup> M <sup>†</sup>	<i>flexlife-10, high flex over 10 million cycles</i>	
	WKC 6T-*/S90/S760	AWM PUR Black 6x24 AWG 105°C 5.7 mm OD Cable #RF50728- <sup>†</sup> M <sup>†</sup>	<i>Cut/Abrasion Immune</i>	
	WKC 6T-*/S529	AWM PVC Yellow 6x24 AWG 105°C 6.2 mm OD Cable #RF51120- <sup>†</sup> M <sup>†</sup>	<i>Cut/Abrasion immune, braided mechanical shield</i>	
	WKC 6T-*/S849/S1052	AWM PVC Grey 6x22 AWG 105°C 6.2 mm OD Cable #RF51284- <sup>†</sup> M <sup>†</sup>	<i>flexlife, 22 AWG conductors, grey cable</i>	
	WKC 6T-*/S618	AWM PVC Grey 6x24 AWG Foil/Drain 105°C 5.7 mm OD Cable #RF50610- <sup>†</sup> M <sup>†</sup>	<i>RFI/EMI Shielding</i>	
	WKC 6T-*/S653	AWM PVC Grey 5x22 AWG Foil/Drain 105°C 5.7 mm OD Cable #RF50609- <sup>†</sup> M <sup>†</sup>		
	WKC 6T-*/S90/CS10476	AWM PUR NAMUR Blue 5x24 AWG Foil/Drain 80°C 5.7 mm OD Cable #RF50928- <sup>†</sup> M <sup>†</sup>	<i>Cut/Abrasion Immune</i>	

\* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

\*\* Standard coupling nut material is nickel plated brass "WKC .."; "WKCV .." indicates 316 stainless steel.

† See Section N for **reelfast**® cable information.