

8-Wire M12 eurofast® Cordsets, "C" Style Medium Plug Body

- Right Angle Female Connector
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection
- 60 VAC/75 VDC, 2 A



Housing Style	Part Number	Cable	Features	Pinout
	WKC 8.6T-*	AWM PVC Black 6x24 AWG Foil/Drain 105°C 5.7mm OD Cable #RF50845-*M†	<i>flexlife® for picofast 4-port multibox</i>	1. WH 2. CN 3. YE 4. GY 5. BN 6. N/C 7. BU 8. N/C
	WKC 8T-*	AWM PVC Grey 8x24 AWG 105°C 5.7 mm OD Cable #RF50753-*M†	<i>flexlife</i>	
	WKC 8T-*/S715	AWM PVC Yellow 8x24 AWG 105°C 5.7 mm OD Cable #RF50884-*M†		
	WKC 8T-*/S90	AWM PUR Grey 8x24 AWG 105°C 5.7 mm OD Cable #RF50984-*M†	<i>Cut/Abrasion Immune</i>	
	WKC 8T-*/S101	AWM TPE Grey 8x24 AWG 105°C 5.7 mm OD Cable #RF50911-*M†	<i>flexlife-10, High Flex Over 10 Million Cycles</i>	
	WKC 8T-*/S618	AWM PVC Grey 8x24 AWG Foil/Drain 105°C 5.7 mm OD Cable #RF50815-*M†		1. WH 2. BN 3. CN 4. YE 5. GY 6. PK 7. BU 8. RD
	WKC 8T-*/S1555	AWM PVC Black 7x24 AWG Foil/Drain 105°C 6.0 mm OD Cable #RF50761-*M†	<i>RFI/EMI Shielding</i>	
	WKC 8.8T-*	AWM PVC Grey 8x24 AWG 105°C 5.7 mm OD Cable #RF50753-*M†	<i>flexlife</i>	1. WH 2. CN 3. YE 4. GY 5. BN 6. PK 7. BU 8. RD

Cordsets

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "WKC .."; "WKCVC .." indicates 316 stainless steel.

† See Section N for **reelfast®** cable information.