

4, 5 and 6-Wire M12 eurofast® Cordsets, "S" Style, Shielded

- Right Angle Male Connector
- Shield to Coupling Nut
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection



Housing Style	Part Number	Cable	Features	Pinout	
	WSS 4.4T-*	AWM PVC Grey 4x22 AWG 105°C 250 V, 4 A 7.3 mm OD Cable #RF50729-*M [†]	RFI/EMI Shielding Tied to Coupling Nut	1. BN 2. WH 3. BU 4. BK	
	WSS 4.4T-*/S90	AWM PUR Grey 4x22 AWG 105°C 250 V, 4 A 7.2 mm OD Cable #RF50810-*M [†]			
	WSS 4.4T-*/S824	PLTC AWM PVC Grey 4x22 AWG 105°C 250 V, 4 A 7.3 mm OD Cable #RF50823-*M [†]	RFI/EMI Shielding Tied to Coupling Nut, Tray Cable Rated		
	WSS 4.5T-*	AWM PVC Grey 5x22 AWG 105°C 250 V, 4 A 7.3 mm OD Cable #RF50713-*M [†]	RFI/EMI Shielding Tied to Coupling Nut	1. BN 2. WH 3. BU 4. BK 5. GY	
	WSS 6T-*	AWM PVC Grey 6x24 AWG 105°C 60 VAC/75 VDC 2 A 7.3 mm OD Cable #RF50814-*M [†]	RFI/EMI Shielding Tied to Coupling Nut	1. BN 2. WH 3. BU 4. BK 5. GY 6. PK	

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "WSS .:"; "WSSV .." indicates 316 stainless steel..

† See Section N for reelfast® cable information.

8, 10 and 12-Wire M12 eurofast® Cordsets, "S" Style, Shielded

- Right Angle Male Connector
- Shield to Coupling Nut
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection



Housing Style	Part Number	Cable	Features	Pinout
	WSS 8T-*	AWM PVC Grey 8x24 AWG 105°C 60 VAC/75 VDC 2 A 7.3 mm OD Cable #RF50813-*M [†]	RFI/EMI Shielding Tied to Coupling Nut	<ol style="list-style-type: none"> 1. WH 2. BN 3. GN 4. YE 5. GY 6. PK 7. BU 8. RD
	WSS 10T-*	AWM PVC Grey 10x24 AWG 105°C 60 VAC/75 VDC 2 A 7.3 mm OD Cable #RF51006-*M [†]	RFI/EMI Shielding Tied to Coupling Nut	<ol style="list-style-type: none"> 1. WH 2. BN 3. GN 4. YE 5. GY 6. PK 7. BU 8. RD 9. OG 10. TN
	WSS 12T-*	AWM PVC Grey 12x24 AWG 105°C 60 VAC/75 VDC 2 A 7.3 mm OD Cable #RF50988-*M [†]	RFI/EMI Shielding Tied to Coupling Nut	<ol style="list-style-type: none"> 1. WH 2. BN 3. GN 4. YE 5. GY 6. PK 7. BU 8. RD 9. OG 10. TN 11. BK 12. VT

Cordsets

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.
 ** Standard coupling nut material is nickel plated brass "WSS .."; "WSSV .." indicates 316 stainless steel..
 † See Section N for **reelfast**® cable information.