

4, 5 and 6-Wire M12 *eurofast*® Cordsets, "S" Style, Shielded

- Right Angle Female Connector
- Shield to Coupling Nut
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection



Housing Style	Part Number	Cable	Features	Pinout
	WKS 4.4T-*	AWM PVC Grey 4x22 AWG 105°C 250 V, 4 A 7.3 mm OD Cable #RF50729-*M <sup>†</sup>	RFI/EMI	
	WKS 4.4T-*/S90	AWM PUR Grey 4x22 AWG 105°C 250 V, 4 A 7.2 mm OD Cable #RF50810-*M <sup>†</sup>		
	WKS 4.4T-*/S824	PLTC PVC Grey 4x22 AWG 105°C 250 V, 4 A 7.3 mm OD Cable #RF50823-*M <sup>†</sup>	RFI/EMI Tray rated	
	WKS 4.5T-*	AWM PVC Grey 5x22 AWG 105°C 250 V, 4 A 7.3 mm OD Cable #RF50713-*M <sup>†</sup>	RFI/EMI	
	WKS 6T-*	AWM PVC Grey 6x24 AWG 105°C, 60 VAC/75 VDC, 2 A 7.3 mm OD Cable #RF50814-*M <sup>†</sup>	RFI/EMI	

\* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

\*\* Standard coupling nut material is nickel plated brass "WKS .."; "WKS SV .." indicates 316 stainless steel..

† See Section N for *reelfast*® cable information.

8, 10 and 12-Wire M12 eurofast® Cordsets, "S" Style, Shielded

- Right Angle Female Connector
- Shield to Coupling Nut
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection



Housing Style	Part Number	Cable	Features	Pinout
	WKS 8T-*	AWM PVC Grey 8x24 AWG 105°C 60 VAC/75 VDC 2 A 7.3 mm OD Cable #RF50813-*M†	RFI/EMI	1. WH 2. BN 3. GN 4. YE 5. GY 6. PK 7. BU 8. RD 
	WKS 10T-*	AWM PVC Grey 10x24 AWG 105°C 60 VAC/75 VDC 2 A 7.3 mm OD Cable #RF51006-*M†	RFI/EMI	1. WH 6. PK 2. BN 7. BU 3. GN 8. RD 4. YE 9. OG 5. GY 10. TN 
	WKS 12T-*	AWM PVC Grey 12x24 AWG 105°C 60 VAC/75 VDC 2 A 7.3 mm OD Cable #RF50988-*M†	RFI/EMI	1. WH 7. BU 2. BN 8. RD 3. GN 9. OG 4. YE 10. TN 5. GY 11. BK 6. PK 12. VT 

Cordsets

\* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.  
 \*\* Standard coupling nut material is nickel plated brass "WKS .."; "WKS.." indicates 316 stainless steel..  
 † See Section N for **reelfast**® cable information.