

M12 eurofast® Spiral Cordsets, Standard Plug Body

- Straight and Right Angle Female Connector
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection



Housing Style	Part Number	Cable	Application	Pinout
RK ...-SP**	RK 4T-3.3/S90-SP	AWM PUR Grey 3x22 AWG 80°C 250 VAC/300 VDC 4 A 5.2 mm OD	For repetitive motion 3-wire DC applications	1. BN 3. BU 4. BK
	RK 4.4T-3.3/S90-SP	AWM PUR Grey 4x22 AWG 80°C 250 VAC/300 VDC 4 A 5.2 mm OD	For repetitive motion 4-wire DC applications	1. BN 2. WH 3. BU 4. BK
	RK 4.4T-3/S90-SP/S669	AWM PUR Black 4x26 AWG 80°C 250 VAC/300 VDC 4 A 4.0 mm OD	For repetitive motion 4-wire DC applications, eurofast connector with picofast coil cord	1. BN 2. WH 3. BU 4. BK
	RK 4.5T-3.3/S90-SP	AWM PUR Grey 5x22 AWG 105°C 250 VAC/300 VDC 4 A 5.7 mm OD	For repetitive motion 5-wire DC applications	1. BN 2. WH 3. BU 4. BK 5. GY
WK ...-SP**	WK 4T-3.3/S90-SP	AWM PUR Grey 3x22 AWG 80°C 250 VAC/300 VDC 4 A 5.2 mm OD	For repetitive motion 3-wire DC applications	1. BN 3. BU 4. BK
	WK 4.4T-3.3/S90-SP	AWM PUR Grey 4x22 AWG 80°C 250 VAC/300 VDC 4 A 5.2 mm OD	For repetitive motion 4-wire DC applications	1. BN 2. WH 3. BU 4. BK
	WK 4.4T-3/S90-SP/S669	AWM PUR Black 4x26 AWG 80°C 250 VAC/300 VDC 4 A 4.0 mm OD	For repetitive motion 4-wire DC applications, eurofast connector with picofast® coil cord	1. BN 2. WH 3. BU 4. BK
	WK 4.5T-3.3/S90-SP	AWM PUR Grey 5x22 AWG 105°C 250 VAC/300 VDC, 4 A 5.7 mm OD	For repetitive motion 5-wire DC applications	1. BN 2. WH 3. BU 4. BK 5. GY

Cordsets

* Length in meters. Standard cable length is 3.3 meters (**picofast** coil standard is 3 meters). Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass .. "RK(WK).."; "RKK(WKK).." indicates nylon and "RKV(WKV)" indicates 316 stainless steel.

M12 eurofast® Spiral Cordsets, Standard Plug Body

- Straight and Right Angle Male Connector
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection



Housing Style	Part Number	Cable	Application	Pinout	
RS ..-SP**	RS 4T-3.3/S90-SP	AWM PUR Grey 3x22 AWG 80°C 250 VAC/300 VDC 4 A 5.2 mm OD	For repetitive motion 3-wire DC applications	1. BN 3. BU 4. BK	
	RS 4.4T-3.3/S90-SP	AWM PUR Grey 4x22 AWG 80°C 250 VAC/300 VDC 4 A 5.2 mm OD	For repetitive motion 4-wire DC applications	1. BN 2. WH 3. BU 4. BK	
	RS 4.4T-3/S90-SP/S669	AWM PUR Black 4x26 AWG 80°C 250 VAC/300 VDC 4 A 4.0 mm OD	For repetitive motion 4-wire DC applications, eurofast connector with picofast coil cord	1. BN 2. WH 3. BU 4. BK	
	RS 4.5T-3.3/S90-SP	AWM PUR Grey 5x22 AWG 105°C 250 VAC/300 VDC 4 A 5.7 mm OD	For repetitive motion 5-wire DC applications	1. BN 2. WH 3. BU 4. BK 5. CY	
WS ..-SP**	WS 4T-3.3/S90-SP	AWM PUR Grey 3x22 AWG 80°C 250 VAC/300 VDC 4 A 5.2 mm OD	For repetitive motion 3-wire DC applications	1. BN 3. BU 4. BK	
	WS 4.4T-3.3/S90-SP	AWM PUR Grey 4x22 AWG 80°C 250 VAC/300 VDC 4 A 5.2 mm OD	For repetitive motion 4-wire DC applications	1. BN 2. WH 3. BU 4. BK	
	WS 4.4T-3/S90-SP/S669	AWM PUR Black 4x26 AWG 80°C 250 VAC/300 VDC 4 A 4.0 mm OD	For repetitive motion 4-wire DC applications, eurofast connector with picofast® coil cord	1. BN 2. WH 3. BU 4. BK	
	WS 4.5T-3.3/S90-SP	AWM PUR Grey 5x22 AWG 105°C 250 VAC/300 VDC 4 A 5.7 mm OD	For repetitive motion 5-wire DC applications	1. BN 2. WH 3. BU 4. BK 5. CY	

* Length in meters. Standard cable length is 3.3 meters (**picofast** coil standard is 3 meters). Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass .. "RS (WS).."; "RSK (WSK).. " indicates nylon and "RSV (WSV)" indicates 316 stainless steel.