

4, 5 and 6-Wire 1/2" *microfast*® Cordsets, Standard Duty

- Right Angle Female Connectors
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 250 V, 4 A



Housing Style	Part Number	Cable	Features	Pinout
	WKB 4T-*	AWM PVC Yellow 4x22 AWG 105°C 5.7 mm OD Cable #RF50555-*M†	<i>flexlife</i> ®	<ol style="list-style-type: none"> <li>RD/BK</li> <li>RD/WH</li> <li>RD</li> <li>GN</li> </ol>
	WKB 4T-*/S90	AWM PUR Yellow 4x22 AWG 105°C 5.7 mm OD Cable #RF50614-*M†	<i>Cut/Abrasion Immune</i>	
	WKB 4T-*/S105	AWM PVC Yellow 4x22 AWG 105°C 5.7 mm OD Cable #RF50656-*M†	<i>Braided Copper Shield</i>	
	WKB 4T-*/S727	AWM PUR Grey 4x22 AWG 105°C 5.2 mm OD Cable #RF50532-*M†	<i>Special Conductor Color Code</i>	<ol style="list-style-type: none"> <li>BN</li> <li>BU</li> <li>BK</li> <li>WH</li> </ol>
	WKB 5T-*	AWM PVC Yellow 5x22 AWG 105°C 5.7 mm OD Cable #RF50556-*M†	<i>flexlife</i>	<ol style="list-style-type: none"> <li>RD/WH</li> <li>RD</li> <li>GN</li> <li>RD/YE</li> <li>RD/BK</li> </ol>
	WKB 6T-*	AWM PVC Yellow 6x22 AWG 105°C 6.2 mm OD Cable #RF51003-*M†	<i>flexlife</i>	<ol style="list-style-type: none"> <li>RD/WH</li> <li>RD</li> <li>GN</li> <li>RD/YE</li> <li>RD/BK</li> <li>RD/BU</li> </ol>

Cordsets

\* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.  
 \*\* Standard coupling nut material is nickel plated brass "WKB .."; "WKBK .." indicates nylon and "WKBV .." indicates 316 stainless steel.  
 † See Section N for *reelfast*® cable information.