

## 4, 5 and 6-Wire 1/2" *microfast*® Cordsets, Standard Duty

- Straight Male Connectors
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 250 V, 4 A



Housing Style	Part Number	Cable	Features	Pinout
	SB 4T-*	AWM PVC Yellow 4x22 AWG 105°C 5.7 mm OD Cable #RF50555-*M†	<i>flexlife</i> ®	
	SB 4T-*/S90	AWM PUR Yellow 4x22 AWG 105°C 5.7 mm OD Cable #RF50614-*M†	<i>Cut/Abrasion Immune</i>	
	SB 4T-*/S105	AWM PVC Yellow 4x22 AWG 105°C 5.7 mm OD Cable #RF50656-*M†	<i>Braided Copper Shield</i>	
	SB 4T-*/S727	AWM PUR Grey 4x22 AWG 105°C 5.2 mm OD Cable #RF50532-*M†	<i>Special conductor color code</i>	
	SB 5T-*	AWM PVC Yellow 5x22 AWG 105°C 5.7 mm OD Cable #RF50556-*M†	<i>flexlife</i>	
	SB 6T-*	AWM PVC Yellow 6x22 AWG 105°C 6.2 mm OD Cable #RF51003-*M†	<i>flexlife</i>	

Cordsets

\* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.  
 \*\* Standard coupling nut material is nickel plated brass "SB .."; "SBK .." indicates nylon and "SBV .." indicates 316 stainless steel.  
 † See Section N for *reelfast*® cable information.