

2 and 3-Wire 7/8" minifast® Cordsets, Heavy Duty

- Right Angle Male Connectors
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 600 VAC/DC, 9 A



Housing Style	Part Number	Cable	Features	Pinout	
<p>WSM ..**</p> <p>2.047 [52.0]</p> <p>1.720 [43.7]</p> <p>7/8-16UN</p> <p>ø1.024 [26.0]</p> <p>WSVH ..**</p> <p>2.047 [52.0]</p> <p>1.689 [42.9]</p> <p>7/8-16UN</p> <p>ø1.063 [27.0]</p>	WSM 26-*M	STOW PVC Yellow 2x16 AWG 105°C 10.4 mm OD Cable #RF50561-*M†	<i>flexlife</i> ®	1. WH 2. BK	
	WSM 35-*M	STOW PVC Yellow 3x16 AWG 105°C 10.4 mm OD Cable #RF50537-*M†	<i>flexlife</i>	1. GN 2. RD/BK 3. RD/WH	
	WSM 35-*M/S600	SOOW CPE Yellow 3x16 AWG 105°C 10.3 mm OD Cable #RF50596-*M†	<i>Weld Flash Immune, Flame Immune</i>	1. GN 2. RD 3. RD	
	WSM 36-*M	STOW PVC Yellow 3x16 AWG 105°C 10.4 mm OD Cable #RF50536-*M†	<i>flexlife</i>	1. GN 2. BK 3. WH	
	WSM 36-*M/S1587	STOW TPE Yellow 3x16 AWG 105°C 10.4 mm OD Cable #RF51563-*M†	<i>weldlife, Weld Flash Immune</i>		

Cordsets

* Length in Meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.
 ** Standard coupling nut material is nickel plated brass "WSM .."; "WS .." indicates nylon, "WSV .." indicates 316 stainless steel, and "WSVH .." indicates 316 stainless steel hex.
 † See Section N for **reelfast**® cable information.

4-Wire 7/8" *minifast*® Cordsets, Heavy Duty

- Right Angle Male Connectors
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 600 VAC/DC, 9 A



Housing Style	Part Number	Cable	Features	Pinout
<p>WSM ..**</p>	WSM 46-*M	STOW PVC Yellow 4x16 AWG 105°C 11 mm OD Cable #RF50538-*M†	<i>flexlife</i>	
	WSM 46-*M/S600	SOOW CPE Yellow 4x16 AWG 105°C 11 mm OD Cable #RF50595-*M†	<i>Weld Flash Immune, Flame Immune</i>	
<p>WSVH ..**</p>	WSM 46-*M/S824	TC PVC Yellow 4x16 AWG 90°C 9.6 mm OD Cable #RF51220-*M†	<i>Tray Rated</i>	
	WSM 46D-*M/S1062	STOW PVC Yellow 6x16 AWG 105°C 13.2 mm OD Cable #RF50565-*M†	<i>flexlife</i> ® Cable, PVC plug body with PVC contact carriers	
	WSM 47-*M	STOW PVC Yellow 4x16 AWG 105°C 13.2 mm OD Cable #RF50626-*M†	<i>flexlife</i>	

* Length in Meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "WSM .."; "WS .." indicates nylon, "WSV .." indicates 316 stainless steel, and "WSVH .." indicates 316 stainless steel hex.

† See Section N for *reelfast*® cable information.

5 and 6-Wire 7/8" *minifast*® Cordsets, Heavy Duty

- Right Angle Male Connectors
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 600 VAC/DC, 9 A



Housing Style	Part Number	Cable	Features	Pinout
	WSM 55-*M	STOW PVC Yellow 5x16 AWG 105°C 13.2 mm OD Cable #RF50540-*M [†]	<i>flexlife</i> ®	1. RD/WH 2. RD/BU 3. GN 4. RD/OG 5. RD/BK
	WSM 55-*M/S600	SOOW CPE Yellow 5x16 AWG 105°C 13 mm OD Cable #RF50597-*M [†]	<i>Weld Flash Immune, Flame Immune</i>	1. RD 2. RD 3. GN 4. RD 5. RD
	WSM 56-*M	STOW PVC Yellow 5x16 AWG 105°C 13.2 mm OD Cable #RF50539-*M [†]	<i>flexlife</i>	1. WH 2. RD 3. GN 4. OG 5. BK
	WSM 56-*M/S1587	STOW TPE Yellow 5x16 AWG 105°C 13.2 mm OD Cable #RF51265-*M [†]	<i>weldlife, Weld Flash Immune</i>	
	WSM 66-*M	STOW PVC Yellow 6x16 AWG 105°C 13.2 mm OD Cable #RF50565-*M [†]	<i>flexlife</i>	1. WH 2. RD 3. GN 4. OG 5. BK 6. BU
	WSM 66-*M/S1587	STOW TPE Yellow 6x16 AWG 105°C 13.7 mm OD Cable #RF51564-*M [†]	<i>weldlife, Weld Flash Immune</i>	

Cordsets

* Length in Meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "WSM .."; "WS .." indicates nylon, "WSV .." indicates 316 stainless steel, and "WSVH .." indicates 316 stainless steel hex.

[†] See Section N for *reelfast*® cable information.