

2-5 Wire 7/8" *minifast*® Cordsets, Smooth Body

- Straight Female Connectors
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 600 V, 9 A



Housing Style	Part Number	Cable	Features	Pinout
<p>RKM ..D**</p>	RKM 26D-*M	STOW PVC Yellow 2x16 AWG 105°C 10.4 mm OD Cable #RF50561-*M [†]	<i>flexlife</i> ®	1. WH 2. BK
	RKM 35D-*M	STOW PVC Yellow 3x16 AWG 105°C 10.4 mm OD Cable #RF50537-*M [†]	<i>flexlife</i>	1. GN 2. RD/BK 3. RD/WH
	RKM 36D-*M	STOW PVC Yellow 3x16 AWG 105°C 10.4 mm OD Cable #RF50536-*M [†]	<i>flexlife</i>	1. GN 2. BK 3. WH
	RKM 46D-*M	STOW PVC Yellow 4x16 AWG 105°C 11 mm OD Cable #RF50538-*M [†]	<i>flexlife</i>	1. BK 2. WH 3. RD 4. GN
	RKM 56D-*M	STOW PVC Yellow 5x16 AWG 105°C 13.2 mm OD Cable #RF50539-*M [†]	<i>flexlife</i>	1. WH 2. RD 3. GN 4. OG 5. BK

* Length in Meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "RKM .."; "RKV .." indicates 316 stainless steel.

† See Section N for *reelfast*® cable information.

2-5 Wire 7/8" *minifast*® Cordsets, Smooth Body

- Straight Male Connectors
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 600 V, 9 A



Housing Style	Part Number	Cable	Features	Pinout
	RSM 26D-*M	STOW PVC Yellow 2x16 AWG 105°C 10.4 mm OD Cable #RF50561-*M [†]	<i>flexlife</i> ®	1. WH 2. BK
	RSM 35D-*M	STOW PVC Yellow 3x16 AWG 105°C 10.4 mm OD Cable #RF50537-*M [†]	<i>flexlife</i>	1. GN 2. RD/BK 3. RD/WH
	RSM 36D-*M	STOW PVC Yellow 3x16 AWG 105°C 10.4 mm OD Cable #RF50536-*M [†]	<i>flexlife</i>	1. GN 2. BK 3. WH
	RSM 46D-*M	STOW PVC Yellow 4x16 AWG 105°C 11 mm OD Cable #RF50538-*M [†]	<i>flexlife</i>	1. BK 2. WH 3. RD 4. GN
	RSM 56D-*M	STOW PVC Yellow 5x16 AWG 105°C 13.2 mm OD Cable #RF50539-*M [†]	<i>flexlife</i>	1. WH 2. RD 3. GN 4. OG 5. BK

Cordsets

* Length in Meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.
 ** Standard coupling nut material is nickel plated brass "RSM .."; "RS .." indicates nylon and "RSV .." indicates 316 stainless steel.
 † See Section N for *reelfast*® cable information.