



12 and 16-Pin M23 multifast® Cordsets, AC and NAMUR Color Codes

- Straight Female Connector
- For *euromast*® Junction Boxes and multi-conductor Applications
- IEC IP 67 Protection



Housing Style	Part Number	Cable	Ports, App.	Features	Pinout
	CKRM 12-6-*	AWM PVC Black 6x18 AWG 105°C 300 V, 6 A 7.2 mm OD Cable #RF50551-.*M†	4 port	flexlife®	1. OG 2. BU 4. BK 5. WH 6. RD 7. GN
	CKRM 12-8-*	AWM PVC Black 8x18 AWG 105°C 300 V, 6 A 10 mm OD Cable #RF50552-.*M†	6 port		1. OG 2. BU 3. YE 4. BK 5. WH 6. RD 7. GN 8. BN
	CKRM 12-10-*	AWM PVC Black 10x18 AWG 105°C 300 V, 6 A 10 mm OD Cable #RF50553-.*M†	8 port		1. VT 2. BU 3. GY 4. BK 5. WH 6. RD 7. GN 8. YE 9. OG 10. BN
	CKNM 12-9-*	PLTC PVC Blue 9x22 AWG 105°C 300 V, 3 A 6.9 mm OD Cable #RF50741-.*M†	4 port, Namur, 1 isolated circuit per port or 2 circuits per port with common positive		1. BN 2. WH 3. BK 4. GN 5. RD 6. OG 7. BU 8. YE 9. VT
	CKNM 16-16-*	PLTC PVC Blue 16x22 AWG 105°C 300 V, 3 A 8.3 mm OD Cable #RF50744-.*M†	4 port, 2 isolated circuits per port		1. WH 2. BK 3. GN 4. RD 5. OG 6. BU 7. BN 8. YE 9. VT 10. GY 11. PK 12. TN 13. WH/BK 14. WH/GN 15. WH/RD 16. WH/BU



* Length in meters.

Standard cable lengths are 5 and 10 meters. Consult factory for other lengths.

Standard coupling nut material is nickel plated brass. "CKR(N)M.."; "CKR(N)MV.." indicates stainless steel coupling nut.

† See Section N for *reelfast*® cable information.