


16-Pin M23 *multifast*® Connectors, DC Color Code, Isolated Power Supply

- Straight Male Connector
- For *eurofast*® Junction Boxes and multi-conductor Applications
- IEC IP 67 Protection
- 150 V, 6 A



Housing Style	Part Number	Cable	Ports, App.	Features	Pinout
	CSSAM 16-10-*	AWM PVC Yellow 10x18 AWG 105°C 10 mm OD Cable #RF50607-*M†	4-port, Dual Supply	flexlife®	1. BN 3. BU 4. WH 5. GN/YE 6. OG 7. YE 8. GY 11. BN/WH 13. BU/WH 15. GN/WH
	CSSAM 16-12-*	AWM PVC Yellow 12x18 AWG 105°C 10 mm OD Cable #RF50606-*M†	6-port, Dual Supply		1. BN 3. BU 4. WH 5. GN/YE 6. OG 7. YE 8. GY 9. PK 10. RD 11. BN/WH 13. BU/WH 15. GN/WH
	CSSAM 16-14-*	AWM PVC Yellow 14x18 AWG 105°C 10.6 mm OD Cable #RF50576-*M†	8-port, Dual Supply		1. BN 3. BU 4. WH 5. GN/YE 6. OG 7. YE 8. GY 9. PK 10. RD 11. BN/WH 12. BK 13. BU/WH 14. VT 15. GN/WH



* Length in meters.
Standard cable lengths are 5 and 10 meters. Consult factory for other lengths.
Standard coupling nut material is nickel plated brass.. "CSSAM.."
† See Section N for *reelfast*® cable information.