


16-Pin M23 multifast® Cordsets, DC Color Code, Isolated Power Supply

- Straight Male Connector
- For *eurofast*®, Junction Boxes and multi-conductor Applications
- IEC IP 67 Protection
- 150 V, 6 A



Housing Style	Part Number	Cable	Ports, App.	Features	Pinout
	CSAM 16-10-*	AWM PVC Yellow 10x18 AWG 105°C 10 mm OD Cable #RF50607-*M [†]	4-port Dual Supply	flexlife®	1. BN 3. BU 4. WH 5. GN/YE 6. OG 7. YE 8. GY 11. BN/WH 13. BU/WH 15. GN/WH
	CSAM 16-12-*	AWM PVC Yellow 12x18 AWG 105°C 10 mm OD Cable #RF50606-*M [†]	6-port Dual Supply		1. BN 3. BU 4. WH 5. GN/YE 6. OG 7. YE 8. GY 9. PK 10. RD 11. BN/WH 13. BU/WH 15. GN/WH
	CSAM 16-14-*	AWM PVC Yellow 14x18 AWG 105°C 10.6 mm OD Cable #RF50576-*M [†]	8-port Dual Supply		1. BN 3. BU 4. WH 5. GN/YE 6. OG 7. YE 8. GY 9. PK 10. RD 11. BN/WH 12. BK 13. BU/WH 14. VT 15. GN/WH



* Length in meters.

Standard cable lengths are 5 and 10 meters. Consult factory for other lengths.

Standard coupling nut material is nickel plated brass. "CSAM.."; "CSAMV.." indicates stainless steel coupling nut.

[†] See Section N for *reelfast*® cable information.