


**16-Pin M23 *multifast*® Cordsets, DC Color Code, Isolated Power Supply**

- Right Angle Female Connector
- For *eurofast*® Junction Boxes and multi-conductor Applications
- IEC IP 67 Protection
- 150 V, 6 A



Housing Style	Part Number	Cable	Ports, App.	Features	Pinout
	CKAWM 16-10-*	AWM PVC Yellow 10x18 AWG 105°C 10 mm OD Cable #RF50607-*M <sup>†</sup>	4-port, Dual Supply	flexlife®	1. BN 3. BU 4. WH 5. GN/YE 6. OG 7. YE 8. GY 11. BN/WH 13. BU/WH 15. GN/WH
	CKAWM 16-12-*	AWM PVC Yellow 12x18 AWG 105°C 10 mm OD Cable #RF50606-*M <sup>†</sup>	6-port, Dual Supply		1. BN 3. BU 4. WH 5. GN/YE 6. OG 7. YE 8. GY 9. PK 10. RD 11. BN/WH 13. BU/WH 15. GN/WH
	CKAWM 16-14-*	AWM PVC Yellow 14x18 AWG 105°C 10.6 mm OD Cable #RF50576-*M <sup>†</sup>	8-port, Dual Supply		1. BN 3. BU 4. WH 5. GN/YE 6. OG 7. YE 8. GY 9. PK 10. RD 11. BN/WH 12. BK 13. BU/WH 14. VT 15. GN/WH



Cordsets

\* Length in meters.  
Standard cable lengths are 5 and 10 meters. Consult factory for other lengths.  
Standard coupling nut material is nickel plated brass.. "CKAWM.."; "CKAWMV.." indicates stainless steel coupling nut.  
<sup>†</sup> See Section N for *reelfast*® cable information.