

26 and 28-Pin M27 multifast® Cordsets

- Female Threads and Pins
- For multi-conductor applications
- IEC IP 67 Protection
- 150 V, 5 A



Housing Style	Part Number	Cable	App.	Pinout																											
<p>DKM ..</p>	DKM 26-631-*	AWM PVC Yellow 25x22 AWG, 1x22 AWG drain 105°C 9.4 mm OD Cable #RF50631-*M†	25-wire DC applications/ flexlife®	<table border="0"> <tr> <td>1. BN</td> <td>14. WH</td> </tr> <tr> <td>2. WH/GY</td> <td>15. BU</td> </tr> <tr> <td>3. BU/GY</td> <td>16. BK/GY</td> </tr> <tr> <td>4. BN/GY</td> <td>17. BN/OG</td> </tr> <tr> <td>5. BK/YE</td> <td>18. WH/OG</td> </tr> <tr> <td>6. WH/YE</td> <td>19. BK/OG</td> </tr> <tr> <td>7. BU/YE</td> <td>20. BK/GN</td> </tr> <tr> <td>8. BN/YE</td> <td>21. WH/GN</td> </tr> <tr> <td>9. BK/RD</td> <td>22. BU/GN</td> </tr> <tr> <td>10. WH/RD</td> <td>23. BN/GN</td> </tr> <tr> <td>11. BU/RD</td> <td>24. BU/OG</td> </tr> <tr> <td>12. BN/RD</td> <td>25. GN/YE</td> </tr> <tr> <td>13. BK</td> <td>26. N/C</td> </tr> </table>	1. BN	14. WH	2. WH/GY	15. BU	3. BU/GY	16. BK/GY	4. BN/GY	17. BN/OG	5. BK/YE	18. WH/OG	6. WH/YE	19. BK/OG	7. BU/YE	20. BK/GN	8. BN/YE	21. WH/GN	9. BK/RD	22. BU/GN	10. WH/RD	23. BN/GN	11. BU/RD	24. BU/OG	12. BN/RD	25. GN/YE	13. BK	26. N/C	
	1. BN				14. WH																										
2. WH/GY	15. BU																														
3. BU/GY	16. BK/GY																														
4. BN/GY	17. BN/OG																														
5. BK/YE	18. WH/OG																														
6. WH/YE	19. BK/OG																														
7. BU/YE	20. BK/GN																														
8. BN/YE	21. WH/GN																														
9. BK/RD	22. BU/GN																														
10. WH/RD	23. BN/GN																														
11. BU/RD	24. BU/OG																														
12. BN/RD	25. GN/YE																														
13. BK	26. N/C																														
DKWM 26-631-*	<p>DKWM ..</p>	27-wire DC applications/ flexlife	<table border="0"> <tr> <td>1. BN</td> <td>15. BU</td> </tr> <tr> <td>2. WH/GY</td> <td>16. BK/GY</td> </tr> <tr> <td>3. BU/GY</td> <td>17. BN/OG</td> </tr> <tr> <td>4. BN/GY</td> <td>18. WH/OG</td> </tr> <tr> <td>5. BK/YE</td> <td>19. BK/OG</td> </tr> <tr> <td>6. WH/YE</td> <td>20. BK/GN</td> </tr> <tr> <td>7. BU/YE</td> <td>21. WH/GN</td> </tr> <tr> <td>8. BN/YE</td> <td>22. BU/GN</td> </tr> <tr> <td>9. BK/RD</td> <td>23. BN/GN</td> </tr> <tr> <td>10. WH/RD</td> <td>24. BU/OG</td> </tr> <tr> <td>11. BU/RD</td> <td>25. GN/YE</td> </tr> <tr> <td>12. BN/RD</td> <td>26. GY</td> </tr> <tr> <td>13. BK</td> <td>27. OG</td> </tr> <tr> <td>14. WH</td> <td>28. N/C</td> </tr> </table>	1. BN	15. BU	2. WH/GY	16. BK/GY	3. BU/GY	17. BN/OG	4. BN/GY	18. WH/OG	5. BK/YE	19. BK/OG	6. WH/YE	20. BK/GN	7. BU/YE	21. WH/GN	8. BN/YE	22. BU/GN	9. BK/RD	23. BN/GN	10. WH/RD	24. BU/OG	11. BU/RD	25. GN/YE	12. BN/RD	26. GY	13. BK	27. OG	14. WH	28. N/C
1. BN				15. BU																											
2. WH/GY	16. BK/GY																														
3. BU/GY	17. BN/OG																														
4. BN/GY	18. WH/OG																														
5. BK/YE	19. BK/OG																														
6. WH/YE	20. BK/GN																														
7. BU/YE	21. WH/GN																														
8. BN/YE	22. BU/GN																														
9. BK/RD	23. BN/GN																														
10. WH/RD	24. BU/OG																														
11. BU/RD	25. GN/YE																														
12. BN/RD	26. GY																														
13. BK	27. OG																														
14. WH	28. N/C																														
DKWM 28-061-*																															

Cordsets

* Length in meters.
 Standard cable lengths are 5 and 10 meters. Consult factory for other lengths.
 Standard coupling nut material is nickel plated brass.. "DKM.." / "DKWM..".
 † See Section N for **reelfast**® cable information.

26 and 28-Pin M27 multifast® Cordsets

- Female Threads and Male Pins
- For multi-conductor applications
- IEC IP 67 Protection
- 150 V, 5 A



Housing Style	Part Number	Cable	App.	Pinout																												
<p>DSM ..</p>	DSM 26-631-*	AWM PVC Yellow 25x22 AWG, 1x22 AWG drain 105°C 9.4 mm OD Cable #RF50631-*M†	25-wire DC applications/ flexlife®	<table border="0"> <tr><td>1. BN</td><td>14. WH</td></tr> <tr><td>2. WH/GY</td><td>15. BU</td></tr> <tr><td>3. BU/GY</td><td>16. BK/GY</td></tr> <tr><td>4. BN/GY</td><td>17. BN/OG</td></tr> <tr><td>5. BK/YE</td><td>18. WH/OG</td></tr> <tr><td>6. WH/YE</td><td>19. BK/OG</td></tr> <tr><td>7. BU/YE</td><td>20. BK/GN</td></tr> <tr><td>8. BN/YE</td><td>21. WH/GN</td></tr> <tr><td>9. BK/RD</td><td>22. BU/GN</td></tr> <tr><td>10. WH/RD</td><td>23. BN/GN</td></tr> <tr><td>11. BU/RD</td><td>24. BU/OG</td></tr> <tr><td>12. BN/RD</td><td>25. GN/YE</td></tr> <tr><td>13. BK</td><td>26. N/C</td></tr> </table>	1. BN	14. WH	2. WH/GY	15. BU	3. BU/GY	16. BK/GY	4. BN/GY	17. BN/OG	5. BK/YE	18. WH/OG	6. WH/YE	19. BK/OG	7. BU/YE	20. BK/GN	8. BN/YE	21. WH/GN	9. BK/RD	22. BU/GN	10. WH/RD	23. BN/GN	11. BU/RD	24. BU/OG	12. BN/RD	25. GN/YE	13. BK	26. N/C		
	1. BN	14. WH																														
2. WH/GY	15. BU																															
3. BU/GY	16. BK/GY																															
4. BN/GY	17. BN/OG																															
5. BK/YE	18. WH/OG																															
6. WH/YE	19. BK/OG																															
7. BU/YE	20. BK/GN																															
8. BN/YE	21. WH/GN																															
9. BK/RD	22. BU/GN																															
10. WH/RD	23. BN/GN																															
11. BU/RD	24. BU/OG																															
12. BN/RD	25. GN/YE																															
13. BK	26. N/C																															
DSWM 26-631-*																																
<p>DSWM ..</p>	DSM 28-061-*	AWM PVC Yellow 27x22 AWG, 1x22 AWG drain 105°C 10 mm OD Cable #RF51061-*M†	27-wire DC applications/ flexlife	<table border="0"> <tr><td>1. BN</td><td>15. BU</td></tr> <tr><td>2. WH/GY</td><td>16. BK/GY</td></tr> <tr><td>3. BU/GY</td><td>17. BN/OG</td></tr> <tr><td>4. BN/GY</td><td>18. WH/OG</td></tr> <tr><td>5. BK/YE</td><td>19. BK/OG</td></tr> <tr><td>6. WH/YE</td><td>20. BK/GN</td></tr> <tr><td>7. BU/YE</td><td>21. WH/GN</td></tr> <tr><td>8. BN/YE</td><td>22. BU/GN</td></tr> <tr><td>9. BK/RD</td><td>23. BN/GN</td></tr> <tr><td>10. WH/RD</td><td>24. BU/OG</td></tr> <tr><td>11. BU/RD</td><td>25. GN/YE</td></tr> <tr><td>12. BN/RD</td><td>26. GY</td></tr> <tr><td>13. BK</td><td>27. OG</td></tr> <tr><td>14. WH</td><td>28. N/C</td></tr> </table>	1. BN	15. BU	2. WH/GY	16. BK/GY	3. BU/GY	17. BN/OG	4. BN/GY	18. WH/OG	5. BK/YE	19. BK/OG	6. WH/YE	20. BK/GN	7. BU/YE	21. WH/GN	8. BN/YE	22. BU/GN	9. BK/RD	23. BN/GN	10. WH/RD	24. BU/OG	11. BU/RD	25. GN/YE	12. BN/RD	26. GY	13. BK	27. OG	14. WH	28. N/C
	1. BN	15. BU																														
2. WH/GY	16. BK/GY																															
3. BU/GY	17. BN/OG																															
4. BN/GY	18. WH/OG																															
5. BK/YE	19. BK/OG																															
6. WH/YE	20. BK/GN																															
7. BU/YE	21. WH/GN																															
8. BN/YE	22. BU/GN																															
9. BK/RD	23. BN/GN																															
10. WH/RD	24. BU/OG																															
11. BU/RD	25. GN/YE																															
12. BN/RD	26. GY																															
13. BK	27. OG																															
14. WH	28. N/C																															
DSWM 28-061-*																																

* Length in meters.
Standard cable lengths are 5 and 10 meters. Consult factory for other lengths.
Standard coupling nut material is nickel plated brass.. "DSM.." / "DSWM..".
† See Section N for **reelfast**® cable information.

26 and 28-Pin M27 multifast® Cordsets

- Male Threads and Pins
- For multi-conductor applications
- IEC IP 67 Protection
- 150 V, 5 A



Housing Style	Part Number	Cable	App.	Pinout
<p>DSSM ..</p>	DSSM 26-631-*	<p>AWM PVC Yellow 25x22 AWG, 1x22 AWG drain 105°C 9.4 mm OD Cable #RF50631-*M†</p>	<p>25-wire DC applications/ flexlife®</p>	
	DSSWM 26-631-*			
<p>DSSWM ..</p>	DSSM 28-061-*	<p>AWM PVC Yellow 27x22 AWG, 1x22 AWG drain 105°C 10 mm OD Cable #RF51061-*M†</p>	<p>27-wire DC applications/ flexlife</p>	
	DSSWM 28-061-*			

Cordsets

* Length in meters.
Standard cable lengths are 5 and 10 meters. Consult factory for other lengths.
Standard coupling material is nickel plated brass.. "DSSM.."/"DSSWM..".
† See Section N for **reelfast**® cable information.