

4-Wire M8 picofast® Cordsets, Snap Lock (Locking Sleeve)

- Straight Female Connectors
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 125 VAC/VDC, 2 A



| Housing Style | Part Number | Cable | Features | Pinout | |
|--|-------------------|---|---|--------|-------------------------------------|
| <p>PKG ..Z**</p> <p>1.260 [32.0]</p> <p>0.404 [10.2]</p> <p>LOCKING SLEEVE</p> | PKG 4Z-* | AWM PVC Yellow 4x26 AWG 105°C 4.4 mm OD Cable #RF50697-*M† | <i>flexlife®</i> | | |
| | PKG 4Z-*/S90 | AWM PUR Black 4x26 AWG 105°C 4.4 mm OD Cable #RF50586-*M† | <i>Cut/Abrasion Immune</i> | | |
| | PKG 4Z-*/S90/S101 | AWM PUR Black 4x26 AWG 105°C 4.4 mm OD Cable #RF50935-*M† | <i>Cut/Abrasion Immune, flexlife-10, High Flex - Over 10 Million Cycles</i> | | 1. BN 2. WH 3. BU 4. BK |
| | PKG 4Z-*/S90/S618 | AWM PUR Black 4x26 AWG 105°C 4.4 mm OD Cable #RF50602-*M† | <i>Cut/Abrasion Immune, EMI/RFI Protection</i> | | |
| | PKG 4Z-*/S760 | AWM PVC Black 4x26 AWG 105°C 4.4 mm OD Cable #RF50870-*M† | <i>flexlife</i> | | |
| | PKG 4Z-*/S90/S653 | AWM PUR Black 3x24 AWG 105°C 4.4 mm OD Cable #RF50601-*M† | <i>Cut/Abrasion Immune, EMI/RFI Protection</i> | | 1. BN 2. Drain 3. BU 4. BK |

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters.

** Standard coupling material is POM.."PKG..Z".

† See Section N for **reelfast**® cable information.