

4-Wire M8 *picofast*® Cordsets, Snap Lock

- Straight Male Connectors
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 125 VAC/30 VDC, 2 A



Housing Style	Part Number	Cable	Features	Pinout
PSG ..**	PSG 4-*	AWM PVC Yellow 4x26 AWG 105°C 4.4 mm OD Cable #RF50697-*M†	<i>flexlife</i> ®	
	PSG 4-*/S90	AWM PUR Black 4x26 AWG 105°C 4.4 mm OD Cable #RF50586-*M†	<i>Cut/Abrasion Immune</i>	
	PSG 4-*/S90/S101	AWM PUR Black 4x26 AWG 105°C 4.4 mm OD Cable #RF50935-*M†	<i>Cut/Abrasion Immune, flexlife-10, High flex - over 10 million cycles</i>	
	PSG 4-*/S90/S618	AWM PUR Black 4x26 AWG 105°C 4.4 mm OD Cable #RF50602-*M†	<i>Cut/Abrasion Immune, EMI/RFI Protection</i>	
	PSG 4-*/S760	AWM PVC Black 4x26 AWG 105°C 4.4 mm OD Cable #RF50870-*M†	<i>flexlife</i>	
	PSG 4-*/S90/S653	AWM PUR Black 3x24 AWG 105°C 4.4 mm OD Cable #RF50601-*M†	<i>Cut/Abrasion Immune, EMI/RFI Protection</i>	

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters.

** Standard coupling material is POM.. "PSG..".

† See Section N for *reelfast*® cable information.