

6-Wire M8 *pico*fast® Cordsets, Threaded Coupling Nut

- Straight Female Connectors
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 125 VAC/VDC, 2 A



Housing Style	Part Number	Cable	Features	Pinout
<p>PKG ..M**</p> <p>PKG ..M**</p>	PKG 6M-*	AWM PVC Yellow 6x26 AWG 105°C 4.5 mm OD Cable #RF50734-*M [†]	<i>flexlife</i> ®	<p>1. BN 2. WH 3. BU 4. BK 5. GY 6. PK</p>
	PKG 6M-*/S90	AWM PUR Black 6x26 AWG 105°C 4.5 mm OD Cable #RF50735-*M [†]	<i>Cut/Abrasion Immune</i>	
	PKG 6M-*/S760	AWM PVC Black 6x26 AWG 105°C 4.5 mm OD Cable #RF51083-*M [†]	<i>flexlife</i>	
	PKG 6M-*/S90/S618	AWM PUR Black 6x26 AWG 105°C 4.5 mm OD Cable #RF51144-*M [†]	<i>Cut/Abrasion Immune</i> <i>EMI/RFI Protection</i>	

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters.

** Standard coupling material is nickel plated brass. "PKG..M"; "PKGV..M" indicates 316 stainless steel.

† See Section N for *reelfast*® cable information.