

3-Wire M8 *picofast*® Cordsets, Snap Lock

- Right Angle Male Connectors
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 125 VAC/VDC, 4 A



Housing Style	Part Number	Cable	Features	Pinout
PSW ..**	PSW 3-*	AWM PVC Yellow 3x24 AWG 105°C 4.4 mm OD Cable #RF50642-*M†	<i>flexlife</i> ®	1. BN 3. BU 4. BK
	PSW 3-*/S90	AWM PUR Black 3x24 AWG 105°C 4.4 mm OD Cable #RF50587-*M†	<i>Cut/Abrasion Immune</i>	
	PSW 3-*/S90/S101	AWM PUR Black 3x24 AWG 105°C 4.5 mm OD Cable #RF51166-*M†	<i>Cut/Abrasion Immune, flexlife-10, High flex - over 10 million cycles</i>	
	PSW 3-*/S90/S618	AWM PUR Black 3x24 AWG 105°C 4.4 mm OD Cable #RF50601-*M†	<i>Cut/Abrasion Immune, EMI/RFI Protection</i>	
	PSW 3-*/S760	AWM PVC Black 3x24 AWG 4.4 mm OD Cable #RF50585-M†	<i>flexlife</i>	
	PSW 3-*/XOR	PVC Orange 3x24 AWG 80°C, 250°C short term 4.4 mm OD Cable #RF04449-*M†	<i>Weld Flash Immune, High Temp. Immune</i>	

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters.

** Standard coupling material is POM..*PSG..".

† See Section N for *reelfast*® cable information.

4-Wire M8 picofast® Cordsets, Snap Lock

- Right Angle Male Connectors
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 125 VAC/30 VDC, 2 A



Housing Style	Part Number	Cable	Features	Pinout
	PSW 4-*	AWM PVC Yellow 4x26 AWG 105°C 4.4 mm OD Cable #RF50697-*M†	<i>flexlife®</i>	
	PSW 4-*/S90	AWM PUR Black 4x26 AWG 105°C 4.4 mm OD Cable #RF50586-*M†	<i>Cut/Abrasion Immune</i>	
	PSW 4-*/S90/S101	AWM PUR Black 4x26 AWG 105°C 4.4 mm OD Cable #RF50935-*M†	<i>Cut/Abrasion Immune, flexlife-10, High flex - over 10 million cycles</i>	
	PSW 4-*/S90/S618	AWM PUR Black 4x26 AWG 105°C 4.4 mm OD Cable #RF50602-*M†	<i>Cut/Abrasion Immune, EMI/RFI Protection</i>	
	PSW 4-*/S760	AWM PVC Black 4x26 AWG 105°C 4.4 mm OD Cable #RF50870-*M†	<i>flexlife</i>	
	PSW 4-*/S90/S653	AWM PUR Black 3x24 AWG 105°C 4.4 mm OD Cable #RF50601-*M†	<i>Cut/Abrasion Immune, EMI/RFI Protection</i>	

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters.

** Standard coupling material is POM.. "PSG..".

† See Section N for **reelfast®** cable information.

6-Wire M8 *picofast*® Cordsets, Snap Lock

- Right Angle Male Connectors
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 125 VAC/VDC, 2 A



Housing Style	Part Number	Cable	Features	Pinout
PSW ..**	PSW 6-*	AWM PVC Yellow 6x26 AWG 105°C 4.5 mm OD Cable #RF50734-*M†	<i>flexlife</i> ®	1. BN 2. WH 3. BU 4. BK 5. CY 6. PK
	PSW 6-*/S90	AWM PUR Black 6x26 AWG 105°C 4.5 mm OD Cable #RF50735-*M†	<i>Cut/Abrasion Immune</i>	
	PSW 6-*/S760	AWM PVC Black 6x26 AWG 105°C 4.5 mm OD Cable #RF51083-*M†	<i>flexlife</i>	
	PSW 6-*/S90/S618	AWM PUR Black 6x26 AWG 105°C 4.5 mm OD Cable #RF51144-*M†	<i>Cut/Abrasion Immune, EMI/RFI Protection</i>	

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters.

** Standard coupling material is POM.. "PSG..".

† See Section N for *reelfast*® cable information.