

3 and 4-Wire M8 picofast® Spiral Cordsets, Snap Lock (Locking Sleeve)

- Straight and Right Angle Female Connectors
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 125 VAC/VDC, 4 A and 2 A



Housing Style	Part Number	Cable	Application	Pinout
PKG ..Z**	PKG 3Z-3/S90-SP	AWM PUR Black 4x26 AWG 80°C 125 VAC/VDC 4 A 4.0 mm OD	For repetitive motion 3-wire applications, snap lock coupling nut	1. BN 3. BU 4. BK
	PKG 4Z-3/S90-SP	AWM PUR Black 4x26 AWG 80°C 125 VAC/VDC 2 A 4.0 mm OD	For repetitive motion 4-wire applications, snap lock coupling nut	1. BN 2. WH 3. BU 4. BK
PKW ..Z**	PKW 3Z-3/S90-SP	AWM PUR Black 4x26 AWG 80°C 125 VAC/VDC 4 A 4.0 mm OD	For repetitive motion 3-wire applications, snap lock coupling nut	1. BN 3. BU 4. BK
	PKW 4Z-3/S90-SP	AWM PUR Black 4x26 AWG 80°C 125 VAC/VDC 2 A 4.0 mm OD	For repetitive motion 4-wire applications, snap lock coupling nut	1. BN 2. WH 3. BU 4. BK

* Length in meters. Standard cable length is 3 meters. Consult factory for other lengths.

** Standard coupling material is POM.."PKG(W)..Z".

3 and 4-Wire M8 *pico*fast® Spiral Cordsets, Snap Lock

- Straight and Right Angle Male Connectors
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 125 VAC/VDC, 4 A and 2 A



Housing Style	Part Number	Cable	Application	Pinout
PSG ..**	PSG 3-3/S90-SP	AWM PUR Black 4x26 AWG 80°C 125 VAC/VDC 4 A 4.0 mm OD	For repetitive motion 3-wire applications, snap lock coupling nut	1. BN 3. BU 4. BK
	PSG 4-3/S90-SP	AWM PUR Black 4x26 AWG 80°C 125 VAC/VDC 2 A 4.0 mm OD	For repetitive motion 4-wire applications, snap lock coupling nut	1. BN 2. WH 3. BU 4. BK
PSW ..**	PSW 3-3/S90-SP	AWM PUR Black 4x26 AWG 80°C 125 VAC/VDC 4 A 4.0 mm OD	For repetitive motion 3-wire applications, snap lock coupling nut	1. BN 3. BU 4. BK
	PSW 4-3/S90-SP	AWM PUR Black 4x26 AWG 80°C 125 VAC/VDC 2 A 4.0 mm OD	For repetitive motion 4-wire applications, snap lock coupling nut	1. BN 2. WH 3. BU 4. BK

* Length in meters. Standard cable length is 3 meters. Consult factory for other lengths.

** Standard coupling material is POM.. "PSG(W)..Z".

3 and 4-Wire M8 picofast® Spiral Cordsets, Threaded Coupling Nut

- Straight and Right Angle Female Connectors
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 125 VAC/VDC, 4 A and 2 A



Housing Style	Part Number	Cable	Application	Pinout
PKG ..M**	PKG 3M-3/S90-SP	AWM PUR Black 4x26 AWG 80° C 125 VAC/VDC 4 A 4.0 mm OD	For repetitive motion 3-wire applications, threaded coupling nut	1. BN 3. BU 4. BK
	PKG 4M-3/S90-SP	AWM PUR Black 4x26 AWG 80° C 125 VAC/VDC 2 A 4.0 mm OD	For repetitive motion 4-wire applications, threaded coupling nut	1. BN 2. WH 3. BU 4. BK
PKW ..M**	PKW 3M-3/S90-SP	AWM PUR Black 4x26 AWG 80° C 125 VAC/VDC 4 A 4.0 mm OD	For repetitive motion 3-wire applications, threaded coupling nut	1. BN 3. BU 4. BK
	PKW 4M-3/S90-SP	AWM PUR Black 4x26 AWG 80° C 125 VAC/VDC 2 A 4.0 mm OD	For repetitive motion 4-wire applications, threaded coupling nut	1. BN 2. WH 3. BU 4. BK

* Length in meters. Standard cable length is 3 meters. Consult factory for other lengths.

** Standard coupling material is nickel plated brass.. "PKG(W)..M"; "PKG(V)..M" indicates 316 stainless steel.

3 and 4-Wire M8 *pico*fast® Cordsets, Threaded Coupling Nut

- Straight and Right Angle Male Connectors
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 125 VAC/VDC, 4 A and 2 A



Housing Style	Part Number	Cable	Application	Pinout
PSG ..M**	PSG 3M-3/S90-SP	AWM PUR Black 4x26 AWG 80° C 125 VAC/VDC 4 A 4.0 mm OD	For repetitive motion 3-wire applications, threaded coupling nut	1. BN 3. BU 4. BK
	PSG 4M-3/S90-SP	AWM PUR Black 4x26 AWG 80° C 125 VAC/VDC 2 A 4.0 mm OD	For repetitive motion 4-wire applications, threaded coupling nut	1. BN 2. WH 3. BU 4. BK
PSW ..M**	PSW 3M-3/S90-SP	AWM PUR Black 4x26 AWG 80° C 125 VAC/VDC 4 A 4.0 mm OD	For repetitive motion 3-wire applications, threaded coupling nut	1. BN 3. BU 4. BK
	PSW 4M-3/S90-SP	AWM PUR Black 4x26 AWG 80° C 125 VAC/VDC 2 A 4.0 mm OD	For repetitive motion 4-wire applications, threaded coupling nut	1. BN 2. WH 3. BU 4. BK

* Length in meters. Standard cable length is 3 meters. Consult factory for other lengths.

** Standard coupling material is nickel plated brass.. "PSG(W)..M"; "PSGV..M" indicates 316 stainless steel.