

3-Wire M8 *pico*fast® Cordsets, with LEDs, Threaded Coupling Nut

- Right Angle Female Connectors
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 10 VAC/30 VDC, 4 A



Housing Style	Part Number	Cable	Features	Pinout
	PKW 3M-P7X2-*	AWM PVC Yellow 3x24 AWG 105°C 4.4 mm OD Cable #RF50642-*M [†]	PNP Signal, <i>flexlife</i> ®	
	PKW 3M-P7X2-*/S90	AWM PUR Black 3x24 AWG 105°C 4.4 mm OD Cable #RF50587-*M [†]	PNP Signal, Cut/Abrasion Immune	
	PKW 3M-P7X2-*/S90/S101	AWM PUR Black 3x26 AWG 105°C 4.4 mm OD Cable #RF50723-*M [†]	PNP Signal, Cut/Abrasion Immune, <i>flexlife</i> -10, High Flex - over 10 Million Cycles	
	PKW 3M-N7X2-*/S90/S618	AWM PUR Black 3x24 AWG 105°C 4.4 mm OD Cable #RF50601-*M [†]	PNP Signal, Cut/Abrasion Immune, EMI/RFI Protection	
	PKW 3M-N7X2-*	AWM PVC Yellow 3x24 AWG 105°C 4.4 mm OD Cable #RF50642-*M [†]	NPN Signal, <i>flexlife</i>	
	PKW 3M-N7X2-*/S90	AWM PUR Black 3x24 AWG 105°C 4.4 mm OD Cable #RF50587-*M [†]	NPN Signal, Cut/Abrasion Immune	
	PKW 3M-N7X2-*/S90/S101	AWM PUR Black 3x26 AWG 105°C 4.4 mm OD Cable #RF50723-*M [†]	NPN Signal, Cut/Abrasion Immune, <i>flexlife</i> -10, High Flex - over 10 Million Cycles	
	PKW 3M-N7X2-*/S90/S618	AWM PUR Black 3x24 AWG 105°C 4.4 mm OD Cable #RF50601-*M [†]	NPN Signal, Cut/Abrasion Immune, EMI/RFI Protection	

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters.

** Standard coupling material is nickel plated brass.

† See Section N for *reelfast*® cable information.

4-Wire M8 picofast® Cordsets, with LEDs, Threaded Coupling Nut

- Right Angle Female Connectors
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 10 VAC/30 VDC, 2 A



Housing Style	Part Number	Cable	Features	Pinout
<p>PKW ..M**</p> <p>YELLOW (OUTPUT)</p> <p>GREEN (POWER)</p> <p>1.089 [27.6]</p> <p>0.650 [16.5]</p> <p>ø.354 [9.0]</p> <p>M8x1</p>	PKW 4M-P7X2-*	AWM PVC Yellow 4x26 AWG 105°C 4.4 mm OD Cable #RF50697-*M†	PNP Signal, flexlife®	<p>1. BN 2. WH 3. BU 4. BK</p>
	PKW 4M-P7X2-*/S90	AWM PUR Black 4x26 AWG 105°C 4.4 mm OD Cable #RF50586-*M†	PNP Signal, Cut/Abrasion Immune	
	PKW 4M-P7X2-*/S90/S101	AWM PUR Black 4x26 AWG 105°C 4.4 mm OD Cable #RF50723-*M†	PNP Signal, Cut/Abrasion Immune, flexlife-10, High Flex - over 10 Million Cycles	
	PKW 4M-P7X2-*/S90/S618	AWM PUR Black 4x26 AWG 105°C 4.4 mm OD Cable #RF50602-*M†	PNP Signal, Cut/Abrasion Immune, EMI/RFI Protection	
	PKW 4M-N7X2-*	AWM PVC Yellow 4x26 AWG 105°C 4.4 mm OD Cable #RF50697-*M†	NPN Signal, flexlife	
	PKW 4M-N7X2-*/S90	AWM PUR Black 4x26 AWG 105°C 4.4 mm OD Cable #RF50586-*M†	NPN Signal, Cut/Abrasion Immune	
	PKW 4M-N7X2-*/S90/S101	AWM PUR Black 4x26 AWG 105°C 4.4 mm OD Cable #RF50723-*M†	NPN Signal, Cut/Abrasion Immune, flexlife-10, High Flex - over 10 Million Cycles	
	PKW 4M-N7X2-*/S90/S618	AWM PUR Black 4x26 AWG 105°C 4.4 mm OD Cable #RF50602-*M†	NPN Signal, Cut/Abrasion Immune, EMI/RFI Protection	

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters.
 ** Standard coupling material is nickel plated brass.
 † See Section N for **reelfast**® cable information.

3-Wire M8 *pico*fast® Cordsets, with LEDs, Threaded Coupling Nut

- Right Angle Male Connectors
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 10 VAC/30 VDC, 4 A



Housing Style	Part Number	Cable	Features	Pinout
	PSW 3M-P7X2-*	AWM PVC Yellow 3x24 AWG 105°C 4.4 mm OD Cable #RF50642-*M [†]	PNP Signal, <i>flexlife</i> ®	
	PSW 3M-P7X2-*/S90	AWM PUR Black 3x24 AWG 105°C 4.4 mm OD Cable #RF50587-*M [†]	PNP Signal, Cut/Abrasion Immune	
	PSW 3M-P7X2-*/S90/S101	AWM PUR Black 3x26 AWG 105°C 4.4 mm OD Cable #RF50723-*M [†]	PNP Signal, Cut/Abrasion Immune, <i>flexlife-10</i> , High Flex - over 10 Million Cycles	

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters.

** Standard coupling material is nickel plated brass.

† See Section N for *reelfast*® cable information.