

2, 3 and 4-Pin M16 *powerfast™* Cordsets

- Female Connectors
- IEC IP 67 Protection



Housing Style	Part Number	Cable	Features	Pinout
<p><b>BKM ..</b> 2.598 [66.0] 0.748 [19.0] M16x0.75</p>	BKM 22-380-*	TC-ER PVC Black 2x12 AWG 105°C 600 V, 18 A 9.8 mm OD Cable #RF51380-*M†	<i>flexlife, Tray Rated-Exposed Run, Dual Keyway</i>	1. WH 2. BK 
	BKM 34-198-*	TC-ER PVC Black 3x14 AWG 105°C 600 V, 15 A 9.6 mm OD Cable #RF51198-*M†	<i>flexlife, Tray Rated-Exposed Run</i>	1. WH 2. GN 3. BK 
	BKM 44-193-*	TC-ER PVC Black 4x14 AWG 105°C 600 V, 15 A 10 mm OD Cable #RF51193-*M†		1. WH 2. GN 3. BK 4. RD 

\* Length in meters. Standard cable lengths are 2, 5 and 10 meters. Consult factory for other lengths.

Standard coupling nut material is nickel plated brass.. "BKM.."; "BKMV.." indicates 316 stainless steel and "BKMK.." indicates nylon.

† See Section N for **reelfast®** cable information.

## 2, 3 and 4-Pin M16 *powerfast*™ Cordsets

- Male Connectors
- IEC IP 67 Protection



Housing Style	Part Number	Cable	Features	Pinout
	BSM 22-380-*	TC-ER PVC Black 2x12 AWG 105°C 600 V, 18 A 9.8 mm OD Cable #RF51380-*M <sup>†</sup>	<i>flexlife, Tray Rated-Exposed Run, Dual Keyway</i>	1. WH 2. BK 
	BSM 34-198-*	TC-ER PVC Black 3x14 AWG 105°C 600 V, 15 A 9.6 mm OD Cable #RF51198-*M <sup>†</sup>	<i>flexlife, Tray Rated-Exposed Run</i>	1. WH 2. GN 3. BK 
	BSM 44-193-*	TC-ER PVC Black 4x14 AWG 105°C 600 V, 15 A 10 mm OD Cable #RF51193-*M <sup>†</sup>		1. WH 2. GN 3. BK 4. RD 

Cordsets

\* Length in meters. Standard cable lengths are 2, 5 and 10 meters. Consult factory for other lengths.  
Standard coupling nut material is nickel plated brass.. "BSM.."; "BSMV.." indicates 316 stainless steel and "BSMK.." indicates nylon.  
<sup>†</sup> See Section N for *reelfast*® cable information.