

5 - 8 Pin M16 versafast® Cordsets

- Right Angle Male Connector
- IEC IP 67 Protection



Housing Style	Part Number	Cable	Application	Features	Pinouts
	BSWM 5-084-*	AWM PVC Yellow 5x18 AWG 105°C 300 VAC/VDC, 8 A 7.0 mm OD Cable #RF51084-*M†	5-wire DC applications	flexlife®	1. BN 2. WH 3. BU 4. BK 5. GY
	BSWM 6-085-*	AWM PVC Yellow 6x18 AWG 105°C 300 VAC/VDC, 7 A 7.5 mm OD Cable #RF51085-*M†	6-wire DC applications		1. BN 2. WH 3. BU 4. BK 5. GY 6. PK
	BSWM 7-086-*	AWM PVC Yellow 7x18 AWG 105°C 125 VAC/VDC, 7 A 7.5 mm OD Cable #RF51086-*M†	7-wire DC applications		1. WH 2. BN 3. GN 4. YE 5. GY 6. PK 7. BU
	BSWM 8-087-*	AWM PVC Yellow 8x18 AWG 105°C 125 VAC/VDC, 7 A 8.5 mm OD Cable #RF51087-*M†	8-wire DC applications		1. WH 2. BN 3. GN 4. YE 5. GY 6. PK 7. BU 8. RD

Cordsets

* Length in meters. Standard cable lengths are 5 and 10 meters. Consult factory for other lengths.
Standard coupling nut material is nickel plated brass.. "BSWM.."; "BSWMV.." indicates 316 stainless steel and "BSWMK.." indicates nylon.
† See Section N for **reelfast**® cable information.

12-Pin M16 *versafast*® Cordsets

- Right Angle Male Connectors
- For *eurofast*® Junction Boxes and multi-conductor applications
- IEC IP 67 Protection
- 125 VAC/VDC, 4 A





Housing Style	Part Number	Cable	Application	Features	Pinout
	BSWM 12-001-*	AWM PUR Black 12x22 AWG 105°C 7.6 mm OD Cable #RF51001-*M†	12-wire DC applications	<i>flexlife</i> ®	
	BSWM 12-967-*	AWM PVC Black 12x22 AWG 105°C 7.6 mm OD Cable #RF50967-*M†			
	BSWM 12-999-*/S101	AWM TPE Black 12x22 AWG 105°C 7.6 mm OD Cable #RF50999-*M†		<i>Flexlife-10, High Flex - Over 10 million cycles</i>	

* Length in meters. Standard cable lengths are 5 and 10 meters. Consult factory for other lengths.
Standard coupling nut material is nickel plated brass. "BSWM.."; "BSWMK.." indicates nylon and "BSWMV.." indicates 316 stainless steel.
† See Section N for *reelfast*® cable information.

14-Pin M16 versafast® Cordsets

- Right Angle Male Connectors
- For *euromast*® Junction Boxes and multi-conductor applications
- IEC IP 67 Protection
- 30 VAC/VDC, 3 A



Housing Style	Part Number	Cable	Application	Features	Pinout
	BSWM 14-002-*	AWM PUR Black 14x22 AWG 105°C 7.6 mm OD Cable #RF51002-*M†	14-wire DC applications	<i>flexlife</i> ®	
	BSWM 14-000-*/S101	AWM TPE Black 14x22 AWG 105°C 7.6 mm OD Cable #RF51000-*M†		<i>Flexlife-10, High Flex - Over 10 million cycles</i>	
	BSWM 14-998-*	AWM PVC Black 14x22 AWG 105°C 7.6 mm OD Cable #RF50998-*M†			
	BSWM 14-755-*	AWM PVC Black 12x24 AWG 105°C 7.0 mm OD Cable #RF50755-*M†	12-wire DC applications	<i>flexlife</i>	

Cordsets


* Length in meters. Standard cable lengths are 5 and 10 meters. Consult factory for other lengths.
Standard coupling nut material is nickel plated brass.. "BSWM.."; "BSWMK.." indicates nylon and "BSWMV.." indicates 316 stainless steel.
† See Section N for *reelfast*® cable information.

14-Pin M16 *versa*fast® Cordsets

- Right Angle Male Connectors
- For *eurofast*®/*picofast*® Junction Boxes and multi-conductor applications
- IEC IP 67 Protection
- 30 VAC/VDC, 3 A



Housing Style	Part Number	Cable	Application	Features	Pinout
	BSWM 14-836-*	AWM PVC Black 10x24 AWG 105°C 7.0 mm OD Cable #RF50836-*M†	10-wire DC applications	flexlife-10, High Flex - Over 10 million cycles	A. N/C C. GY E. GN G. BK J. N/C L. N/C M. BN N. PK O. YE P. WH R. RD S. VT T. N/C U. BU
	BSWM 14-954-*/S101	AWM TPE Black 10x24 AWG 105°C 7.0 mm OD Cable #RF50954-*M†			12-wire DC applications
	BSWM 14-917-*	AWM PVC Yellow 12x24 AWG 105°C 7.0 mm OD Cable #RF50917-*M†			



* Length in meters. Standard cable lengths are 5 and 10 meters. Consult factory for other lengths.
Standard coupling nut material is nickel plated brass.. "BSWM.."; "BSWMK.." indicates nylon and "BSWMV.." indicates 316 stainless steel.
† See Section N for *reelfast*® cable information.

19-Pin M16 versafast® Cordsets

- Right Angle Male Connectors
- For eurofast®/picofast® Junction Boxes and multi-conductor applications
- IEC IP 67 Protection
- 30 VAC/VDC, 3 A



Housing Style	Part Number	Cable	Application	Features	Pinout
	BSWM 19-873-*	AWM PVC Black 19x26 AWG 105°C 7.1 mm OD Cable #RF50873-*M†	19-wire DC applications	flexlife®	A. RD/BU B. WH/GN C. GY D. BN/GN E. GN F. GN/YE G. BK H. WH/YE I. WH/GY K. GY/BN L. GY/PK M. BN N. PK O. YE P. WH R. RD S. VT T. YE/BN U. BU
	BSWM 19-995-*	AWM PVC Black 19x22 AWG 105°C 8.5 mm OD Cable #RF50995-*M†	19-wire DC applications	Cut/Abrasion Immune	
	BSWM 19-996-*/S90	AWM PUR Black 19x22 AWG 105°C 8.5 mm OD Cable #RF50996-*M†			
	BSWM 19-997-*/S101	AWM TPE Black 19x22 AWG 105°C 8.5 mm OD Cable #RF50997-*M†			

Cordsets

* Length in meters. Standard cable lengths are 5 and 10 meters. Consult factory for other lengths.
 Standard coupling nut material is nickel plated brass.. "BSWM.."; "BSWMK.." indicates nylon and "BSWMV.." indicates 316 stainless steel.
 † See Section N for reelfast® cable information.