

5 - 8 Pin M16 versafast® Cordsets

- Right Angle Female Connector
- IEC IP 67 Protection



Housing Style	Part Number	Cable	Application	Features	Pinouts
	BKWM 5-084-*	AWM PVC Yellow 5x18 AWG 105°C 300 VAC/VDC, 8 A 7.0 mm OD Cable #RF51084-*M†	5-wire DC applications	flexlife®	1. BN 2. WH 3. BU 4. BK 5. GY 
	BKWM 6-085-*	AWM PVC Yellow 6x18 AWG 105°C 300 VAC/VDC, 7 A 7.5 mm OD Cable #RF51085-*M†	6-wire DC applications		1. BN 2. WH 3. BU 4. BK 5. GY 6. PK 
	BKWM 7-086-*	AWM PVC Yellow 7x18 AWG 105°C 125 VAC/VDC, 7 A 7.5 mm OD Cable #RF51086-*M†	7-wire DC applications		1. WH 2. BN 3. GN 4. YE 5. GY 6. PK 7. BU 
	BKWM 8-087-*	AWM PVC Yellow 8x18 AWG 105°C 125 VAC/VDC, 7 A 8.5 mm OD Cable #RF51087-*M†	8-wire DC applications		1. WH 2. BN 3. GN 4. YE 5. GY 6. PK 7. BU 8. RD 

Cordsets

\* Length in meters. Standard cable lengths are 5 and 10 meters. Consult factory for other lengths.  
Standard coupling nut material is nickel plated brass.. "BKWM.."; "BKWMV.." indicates 316 stainless steel and "BKWMK.." indicates nylon.  
† See Section N for reelfast® cable information.

**12-Pin M16 *versafast*® Cordsets**

- Right Angle Female Connectors
- For *eurofast*® Junction Boxes and multi-conductor applications
- IEC IP 67 Protection
- 125 VAC/VDC, 4 A



Housing Style	Part Number	Cable	Application	Features	Pinout
<p><b>BKWM ..</b></p>	BKWM 12-001-*	AWM PUR Black 12x22 AWG 105°C 7.6 mm OD Cable #RF51001- <sup>†</sup> M <sup>†</sup>	12-wire DC applications	<i>flexlife</i> ®	
	BKWM 12-967-*	AWM PVC Black 12x22 AWG 105°C 7.6 mm OD Cable #RF50967- <sup>†</sup> M <sup>†</sup>			
	BKWM 12-999-*/S101	AWM TPE Black 12x22 AWG 105°C 7.6 mm OD Cable #RF50999- <sup>†</sup> M <sup>†</sup>		<i>Flexlife-10, High Flex - Over 10 million cycles</i>	


\* Length in meters. Standard cable lengths are 5 and 10 meters. Consult factory for other lengths.  
Standard coupling nut material is nickel plated brass. "BKWM.."; "BKWMK.." indicates nylon and "BKWMV.." indicates 316 stainless steel.  
<sup>†</sup> See Section N for *reelfast*® cable information.

## 14-Pin M16 versafast® Cordsets

- Right Angle Female Connectors
- For *euromast*® Junction Boxes and multi-conductor applications
- IEC IP 67 Protection
- 30 VAC/VDC, 3 A



Housing Style	Part Number	Cable	Application	Features	Pinout
<p>BKWM ..</p>	BKWM 14-002-*	AWM PUR Black 14x22 AWG 105°C 7.6 mm OD Cable #RF51002-*M†	14-wire DC applications	<i>flexlife</i> ®	A. BN C. RD/BU E. BK G. PK J. GN L. BU M. OG N. GY/BN O. VT P. WH R. RD S. GY T. YE U. TN
	BKWM 14-000-*/S101	AWM TPE Black 14x22 AWG 105°C 7.6 mm OD Cable #RF51000-*M†		<i>Flexlife-10, High Flex - Over 10 million cycles</i>	
	BKWM 14-998-*	AWM PVC Black 14x22 AWG 105°C 7.6 mm OD Cable #RF50998-*M†			
	BKWM 14-755-*	AWM PVC Black 12x24 AWG 105°C 7.0 mm OD Cable #RF50755-*M†	12-wire DC applications	<i>flexlife</i>	A. N/C C. OG E. BK G. GN J. GY L. N/C M. BN N. TN O. VT P. RD R. WH S. YE T. PK U. BU



Cordsets

\* Length in meters. Standard cable lengths are 5 and 10 meters. Consult factory for other lengths.  
Standard coupling nut material is nickel plated brass.. "BKWM.."; "BKWMK.." indicates nylon and "BKWMV.." indicates 316 stainless steel.  
† See Section N for *reelfast*® cable information.

**14-Pin M16 versafast® Cordsets**

- Right Angle Female Connectors
- For eurofast®/picofast® Junction Boxes and multi-conductor applications
- IEC IP 67 Protection
- 30 VAC/VDC, 3 A



Housing Style	Part Number	Cable	Application	Features	Pinout
<p>BKWM ..</p>	BKWM 14-836-*	AWM PVC Black 10x24 AWG 105°C 7.0 mm OD Cable #RF50836-*M†	10-wire DC applications, junction box VB 803M(Z)-BS14	flexlife®	
	BKWM 14-954-*/S101	AWM TPE Black 10x24 AWG 105°C 7.0 mm OD Cable #RF50954-*M†		Flexlife-10, High Flex - Over 10 million cycles	
	BKWM 14-917-*	AWM PVC Yellow 12x24 AWG 105°C 7.0 mm OD Cable #RF50917-*M†	12-wire DC applications, junction boxes 4MBM12-5-BS14 & VB 404M(Z)-BS14	flexlife	

\* Length in meters. Standard cable lengths are 5 and 10 meters. Consult factory for other lengths.  
Standard coupling nut material is nickel plated brass.. "BKWM.."; "BKWMK.." indicates nylon and "BKWMV.." indicates 316 stainless steel.  
† See Section N for reelfast® cable information.

**19-Pin M16 versafast® Cordsets**

- Right Angle Female Connectors
- For eurofast®/picofast® Junction Boxes and multi-conductor applications
- IEC IP 67 Protection
- 30 VAC/VDC, 3 A



Housing Style	Part Number	Cable	Application	Features	Pinout
<p>BKWM ..</p>	BKWM 19-873-*	AWM PVC Black 19x26 AWG 105°C 7.1 mm OD Cable #RF50873-*M†	19-wire DC applications	flexlife®	A. RD/BU B. WH/GN C. GY D. BN/GN E. GN F. GN/YE G. BK H. WH/YE I. WH/GY K. GY/BN L. GY/PK M. BN N. PK O. YE P. WH R. RD S. VT T. YE/BN U. BU
	BKWM 19-995-*	AWM PVC Black 19x22 AWG 105°C 8.5 mm OD Cable #RF50995-*M†	19-wire DC applications & junction box VB 804M(Z)-BS19	Cut/Abrasion Immune	
	BKWM 19-996-*/S90	AWM PUR Black 19x22 AWG 105°C 8.5 mm OD Cable #RF50996-*M†			
	BKWM 19-997-*/S101	AWM TPE Black 19x22 AWG 105°C 8.5 mm OD Cable #RF50997-*M†			

\* Length in meters. Standard cable lengths are 5 and 10 meters. Consult factory for other lengths.  
 Standard coupling nut material is nickel plated brass.. "BKWM.."; "BKWMK.." indicates nylon and "BKWMV.." indicates 316 stainless steel.  
 † See Section N for reelfast® cable information.