

2 and 3-Wire *minifast*® Receptacles, Front Mount, 1/2-14 NPSM Threads

- Female Receptacles
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 600 V, 9 A



Drawing Number	Part Number	Lead Specs.	Features	Pinout	
<p>RKF ..**</p>	RKF 20-*M	UL, CSA 2x18 AWG 105°C	1/2-14NPSM Threads, Standard Duty	1. BN 2. BU	
	RKF 26-*M	UL, CSA 2x16 AWG Leads 105°C	1/2-14NPSM Threads, Heavy Duty	1. WH 2. BK	
	RKF 28-*M	UL, CSA 2x18 AWG 105°C 600 V, 9 A	1/2-14NPSM Threads, Heavy Duty	1. WH 2. BK	
	RKF 30-*M	UL, CSA 3x18 AWG 105°C	1/2-14NPSM Threads, Standard Duty	1. GY/YE 2. BN 3. BU	
	RKF 31-*M	UL, CSA 3x18 AWG 105°C	1/2-14NPSM Threads, Standard Duty	1. BK 2. BN 3. BU	
	RKF 311-*M	UL, CSA 3x18 AWG 105°C	Automotive Color Code 1/2-14NPSM Threads		
	RKF 35-*M	UL, CSA 3x16 AWG 105°C	Automotive Color Code 1/2-14NPSM Threads		1. GN 2. RD/BK 3. RD/WH
	RKF 36-*M	UL, CSA 3x16 AWG 105°C	1/2-14NPSM Threads, Heavy Duty		1. GN 2. BK 3. WH
	RKF 38-*M	UL, CSA 3x18 AWG 105°C 600 V, 9 A	1/2-14NPSM Threads, Heavy Duty	1. GN 2. BK 3. WH	

See page F71 for dimensional drawings.

Standard lead length is 0.5 Meters. Consult factory for other lengths.

** Standard housing material is nickel plated cast zinc. "RKF .."; "RKFV .." indicates 316 stainless steel housing and "RKF .." indicates nylon housing.

For locknuts to be included, add "W/LN" to the end of the part number.

To specify PVC jacketed cable, add "/S717" to the end of the part number.

2 and 3-Wire *minifast*® Receptacles, Front Mount, 1/2-14 NPT Threads

- Female Receptacles
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 600 V, 9 A



Drawing Number	Part Number	Lead Specs.	Features	Pinout
<p>RKF ..**/NPT</p>	RKF 20-*M/NPT	UL, CSA 2x18 AWG 105°C	1/2-14NPT Threads, Standard Duty	1. BN 2. BU
	RKF 26-*M/NPT	UL, CSA 2x16 AWG Leads 105°C	1/2-14NPT Threads, Heavy Duty	1. WH 2. BK
	RKF 30-*M/NPT	UL, CSA 3x18 AWG 105°C	1/2-14NPT Threads, Standard Duty	1. GN/YE 2. BN 3. BU
	RKF 31-*M/NPT	UL, CSA 3x18 AWG 105°C	1/2-14NPT Threads, Standard Duty	1. BK 2. BN 3. BU
	RKF 311-*M/NPT	UL, CSA 3x18 AWG 105°C	Automotive Color Code 1/2-14NPT Threads	1. GN 2. RD/BK 3. RD/WH
	RKF 35-*M/NPT	UL, CSA 3x16 AWG 105°C	Automotive Color Code 1/2-14NPT Threads	
	RKF 36-*M/NPT	UL, CSA 3x16 AWG 105°C	1/2-14NPT Threads, Heavy Duty	1. GN 2. BK 3. WH

Receptacles

See page F71 for dimensional drawings.

Standard lead length is 0.5 Meters. Consult factory for other lengths.

** Standard housing material is nickel plated cast zinc. "RKF .."; "RKFV .." indicates 316 stainless steel housing.

For locknuts to be included, add "W/LN" to the end of the part number.

To specify PVC jacketed cable, add "/S717" to the end of the part number.