

5-Wire *minifast*® Receptacles, Front Mount, 1/2-14 NPSM Threads

- Female Receptacles
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 600 V, 9 A



Drawing Number	Part Number	Lead Specs.	Features	Pinout
<p>RKF ..**</p>	RKF 50-*M	UL, CSA 5x18 AWG 105°C	1/2-14NPSM Threads, Standard Duty	1. BK 2. BU 3. GN/YE 4. BN 5. WH
	RKF 50-*M/S849	UL, CSA 5x22 AWG 105°C 300 V		
	RKF 511-*M	UL, CSA 5x18 AWG 105°C	Automotive Color Code 1/2-14NPSM Threads	1. RD/WH 2. RD/BU 3. GN 4. RD/OG 5. RD/BK
	RKF 511-*M/S849	UL, CSA 5x22 AWG 105°C 300 V		
	RKF 55-*M	UL, CSA 5x16 AWG 105°C	Automotive Color Code 1/2-14NPSM Threads	1. RD/WH 2. RD/BU 3. GN 4. RD/OG 5. RD/BK
	RKF 56-*M	UL, CSA 5x16 AWG 105°C	1/2-14NPSM Threads, Heavy Duty	1. WH 2. RD 3. GN 4. OG 5. BK
	RKF 58-*M	UL, CSA 5x18 AWG 105°C 300 V, 9 A		

See page F71 for dimensional drawings.

Standard lead length is 0.5 Meters. Consult factory for other lengths.

** Standard housing material is nickel plated cast zinc.. "RKF .."; "RKfV .." indicates 316 stainless steel housing and "RKfK .." indicates nylon housing.




For locknuts to be included, add "W/LN" to the end of the part number.

To specify PVC jacketed cable, add "/S717" to the end of the part number.

5 and 6-Wire *minifast*® Receptacles, Front Mount, 1/2-14 NPT Threads

- Female Receptacles
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 600 V, 9 A



Drawing Number	Part Number	Lead Specs.	Features	Pinout
 <p>RKF .. **/NPT</p>	RKF 50-*M/NPT	UL, CSA 5x18 AWG 105°C	1/2-14NPT Threads, Standard Duty	1. BK 2. BU 3. GN/YE 4. BN 5. WH
	RKF 511-*M/NPT	UL, CSA 5x18 AWG 105°C	Automotive Color Code 1/2-14NPT Threads	
	RKF 55-*M/NPT	UL, CSA 5x16 AWG 105°C	Automotive Color Code 1/2-14NPT Threads	
	RKF 56-*M/NPT	UL, CSA 5x16 AWG 105°C	1/2-14NPT Threads, Heavy Duty	1. WH 2. RD 3. GN 4. OG 5. BK
	RKF 58-*M/NPT	UL, CSA 5x18 AWG 105°C 300 V, 9 A		
	RKF 61-*M/NPT	UL, CSA 6x18 AWG 105°C	1/2-14NPT Threads, Standard Duty	1. GN 2. WH 3. BU 4. GY 5. YE 6. BN
	RKF 66-*M/NPT	UL, CSA 6x16 AWG 105°C	1/2-14NPT Threads, Heavy Duty	
	RKF 68-*M/NPT	UL, CSA 6x18 AWG 105°C 600 V, 9 A		

Receptacles

See page F71 for dimensional drawings.

Standard lead length is 0.3 Meters. Consult factory for other lengths.

** Standard housing material is nickel plated cast zinc. "RKF .."; "RKFV .." indicates 316 stainless steel housing.

For locknuts to be included, add "W/LN" to the end of the part number.

To specify PVC jacketed cable, add "/S717" to the end of the part number.