









6, 7 and 8-Wire *minifast*® B-Size Receptacles, Front Mount

- Male Receptacles
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection
- 600 V, 8 A



Drawing Number	Part Number	Lead Specs.	Features	Pinout
 <p>B-Size RSF ..**1/2-14/NPT</p>	RSF 6B6-*M/14.5/NPT	6x16 AWG 105°C	1/2-14NPT Threads	<ol style="list-style-type: none"> OG BU BK WH RD GN 
	RSF 76-*M/14.5/NPT	7x16 AWG 105°C	1/2-14NPT Threads	<ol style="list-style-type: none"> WH/BK BK WH RD OG BU GN 
	RSF 86-*M/14.5/NPT	8x16 AWG 105°C	1/2-14NPT Threads	<ol style="list-style-type: none"> OG BU WH/BK BK WH RD GN RD/BK 
 <p>B-Size RSF ..**3/4-14/NPT</p>	RSF 6B6-*M/14.75/NPT	6x16 AWG 105°C	3/4-14NPT Threads	<ol style="list-style-type: none"> OG BU BK WH RD GN 
	RSF 76-*M/14.75/NPT	7x16 AWG 105°C	3/4-14NPT Threads	<ol style="list-style-type: none"> WH/BK BK WH RD OG BU GN 
	RSF 86-*M/14.75/NPT	8x16 AWG 105°C	3/4-14NPT Threads	<ol style="list-style-type: none"> OG BU WH/BK BK WH RD GN RD/BK 

See page F72 for dimensional drawings.

Standard lead length is 0.3 Meters. Consult factory for other lengths.

** Standard housing material is nickel plated cast zinc. "RSF .."; "RSFV .." indicates 316 stainless steel housing.

For locknuts to be included, add "W/LN" to the end of the part number.

To specify PVC jacketed cable, add "/S717" to the end of the part number.

6, 7 and 8-Wire *minifast*® B-Size Receptacles, Front Mount

- Female Receptacles
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection
- 600 V, 8 A



Drawing Number	Part Number	Lead Specs.	Features	Pinout
<p>9</p> <p>RKF ..**/14.5/NPT</p>	RKF 6B6-*M/14.5/NPT	6x16 AWG 105°C	1/2-14 NPT Threads	1. OG 2. BU 3. BK 4. WH 5. RD 6. GN
	RKF 76-*M/14.5/NPT	7x16 AWG 105°C	1/2-14 NPT Threads	1. WH/BK 2. BK 3. WH 4. RD 5. OG 6. BU 7. GN
	RKF 86-*M/14.5/NPT	8x16 AWG 105°C	1/2-14 NPT Threads	1. OG 2. BU 3. WH/BK 4. BK 5. WH 6. RD 7. GN 8. RD/BK
<p>10</p> <p>RKF ..**/14.75/NPT</p>	RKF 6B6-*M/14.75/NPT	6x16 AWG 105°C	3/4-14 NPT Threads	1. OG 2. BU 3. BK 4. WH 5. RD 6. GN
	RKF 76-*M/14.75/NPT	7x16 AWG 105°C	3/4-14 NPT Threads	1. WH/BK 2. BK 3. WH 4. RD 5. OG 6. BU 7. GN
	RKF 86-*M/14.75/NPT	8x16 AWG 105°C	3/4-14 NPT Threads	1. OG 2. BU 3. WH/BK 4. BK 5. WH 6. RD 7. GN 8. RD/BK

Receptacles

See page F72 for dimensional drawings.

Standard lead length is 0.5 Meters. Consult factory for other lengths.

** Standard housing material is nickel plated cast zinc. "RKF .."; "RKFV .." indicates 316 stainless steel housing.

For locknuts to be included, add "W/LN" to the end of the part number.

To specify PVC jacketed cable, add "/S717" to the end of the part number.