

9, 10 and 12-Wire *minifast*® C-Size Receptacles, Front Mount

- Male Receptacles
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection
- 600 V, 8 A



Drawing Number	Part Number	Lead Specs.	Features	Pinout
<p><b>11</b></p> <p>C-Size RSF .. **1/2-14 NPT</p>	RSF 96-*M/14.5/NPT	9x16 AWG 105°C	1/2-14 NPT Threads	1. OG    6. RD 2. BU    7. GN 3. RD/BK 8. WH/BK 4. GN/BK 9. BK 5. WH 
	RSF 106-*M/14.5/NPT	10x16 AWG 105°C	1/2-14 NPT Threads	1. OG    6. OG/BK 2. BU    7. RD 3. WH/BK 8. GN 4. RD/BK 9. BK 5. GN/BK 10. WH 
	RSF 126-*M/14.5/NPT	12x16 AWG 105°C	1/2-14 NPT Threads	1. OG    7. BU/BK 2. BU    8. BK/WH 3. WH/BK 9. GN 4. RD/BK 10. RD 5. GN/BK 11. WH 6. OG/BK 12. BK 
<p><b>12</b></p> <p>C-Size RSF .. **3/4-14 NPT</p>	RSF 96-*M/14.75/NPT	9x16 AWG 105°C	3/4-14 NPT Threads	1. OG    6. RD 2. BU    7. GN 3. RD/BK 8. WH/BK 4. GN/BK 9. BK 5. WH 
	RSF 106-*M/14.75/NPT	10x16 AWG 105°C	3/4-14 NPT Threads	1. OG    6. OG/BK 2. BU    7. RD 3. WH/BK 8. GN 4. RD/BK 9. BK 5. GN/BK 10. WH 
	RSF 126-*M/14.75/NPT	12x16 AWG 105°C	3/4-14 NPT Threads	1. OG    7. BU/BK 2. BU    8. BK/WH 3. WH/BK 9. GN 4. RD/BK 10. RD 5. GN/BK 11. WH 6. OG/BK 12. BK 

See page F72 for dimensional drawings.

Standard lead length is 0.3 Meters. Consult factory for other lengths.

\*\* Standard housing material is nickel plated cast zinc.. "RSF .."; "RSFV .." indicates 316 stainless steel housing.






For locknuts to be included, add "W/LN" to the end of the part number.

To specify PVC jacketed cable, add "/S717" to the end of the part number.

19-Wire *minifast*® C-Size Receptacles, Front Mount

- Male Receptacles
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection



Drawing Number	Part Number	Lead Specs.	Features	Pinout
<p><b>11</b></p>  <p>RSF .. **1/2-14 NPT</p>	RSF 190-*M/14.5/NPT	3x18, 16x22 AWG 105°C 300 VAC/VDC 4 A (pins 5, 7, & 12) 2 A (all other pins)	1/2-14NPT Threads	
<p><b>12</b></p>  <p>RSF .. **3/4-14 NPT</p>	RSF 190-*M/14.75/NPT	3x18, 16x22 AWG 105°C 300 VAC/VDC 4 A (pins 5, 7, & 12) 2 A (all other pins)	3/4-14NPT Threads	
<p><b>15</b></p>  <p>RSF .. **/PG 16</p>	RSF 190-*M/PG 16	3x18, 16x22 AWG 105°C 300 VAC/VDC 4 A (pins 5, 7, & 12) 2 A (all other pins)	PG 16 Threads	
<p><b>17</b></p>  <p>RSF .. **/M20</p>	RSF 190-*M/M20	3x18, 16x22 AWG 105°C 300 VAC/VDC 4 A (pins 5, 7, & 12) 2 A (all other pins)	M20 Threads	

Receptacles

See page F73 for dimensional drawings.

Standard lead length is 0.5 Meters. Consult factory for other lengths.

\*\* Standard housing material is nickel plated cast zinc. "RSF .."; "RSFV .." indicates 316 stainless steel housing.

For locknuts to be included, add "W/LN" to the end of the part number.

To specify PVC jacketed cable, add "/S717" to the end of the part number.