

3 and 4-Wire M5 pentafast® Receptacles

- Female Receptacle
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 125 V, 1 A



Housing Style	Part Number	Lead Specs.	Application	Pinout
<p>Typical panel cutout is 5.1 mm</p>	VFK 3-*	3x26 AWG 80° C	Mates with 3-pin cordsets	<ol style="list-style-type: none"> 1. BN 2. N/C 3. BU 4. BK
	VFK 4-*	4x26 AWG 80° C	Mates with 4-pin cordsets	<ol style="list-style-type: none"> 1. BN 2. WH 3. BU 4. BK

* Length in meters. Standard lead lengths are 2, 3, 4 and 6 meters. Consult factory for other lengths.
Standard housing material is nickel plated brass.

3 and 4-Wire M5 pentafast® Receptacles

- Male Receptacle
- NEMA 1, 3, 4, 6P
- IEC IP 67 Protection
- 125 V, 1 A



Housing Style	Part Number	Lead Specs.	Application	Pinout
	VFS 3-*	3x26 AWG 80° C	Mates with 3-pin cordsets	1. BN 2. N/C 3. BU 4. BK
	VFS 4-*	4x26 AWG 80° C	Mates with 4-pin cordsets	1. BN 2. WH 3. BU 4. BK

* Length in meters. Standard lead lengths are 2, 3, 4 and 6 meters. Consult factory for other lengths. Standard housing material is nickel plated brass.