

MALE END VIEW	PANEL CUTOUT	LOCKNUT	SPECIFICATIONS																																												
<p>1 = BLACK 2 = GREEN 3 = RED 4 = WHITE</p>	<p>Ø27.0 [Ø1.063]</p>	<p>3/4-14 1 1/4" HEX STOCK 35.9 [1.41] REF. 6.0 [0.24]</p>	<table border="1"> <tr><td>CONTACT CARRIER MATERIAL</td><td>PVC</td></tr> <tr><td>CONTACT MATERIAL/PLATING</td><td>BRASS or COPPER/GOLD</td></tr> <tr><td>HOUSING MATERIAL/FINISH</td><td>STAINLESS STEEL/PASSIVATED</td></tr> <tr><td>GASKET MATERIAL</td><td>NITRILE (BUNA-N)</td></tr> <tr><td>RATED CURRENT [A]</td><td>25 A</td></tr> <tr><td>RATED VOLTAGE [V]</td><td>600 V</td></tr> <tr><td>CONDUCTOR INSULATION MATERIAL</td><td>PVC</td></tr> <tr><td>NUMBERS OF CONDUCTORS [AWG]</td><td>4x10 AWG</td></tr> <tr><td>TEMPERATURE RATING</td><td>-40°C to +105°C (-40°F to +221°F)</td></tr> <tr><td>PROTECTION CLASS</td><td>MEETS NEMA 1,3,4,6P AND IEC IP67, IP68, IP69K</td></tr> <tr><td>MAXIMUM PANEL THICKNESS</td><td>6.0mm [.236]</td></tr> </table>	CONTACT CARRIER MATERIAL	PVC	CONTACT MATERIAL/PLATING	BRASS or COPPER/GOLD	HOUSING MATERIAL/FINISH	STAINLESS STEEL/PASSIVATED	GASKET MATERIAL	NITRILE (BUNA-N)	RATED CURRENT [A]	25 A	RATED VOLTAGE [V]	600 V	CONDUCTOR INSULATION MATERIAL	PVC	NUMBERS OF CONDUCTORS [AWG]	4x10 AWG	TEMPERATURE RATING	-40°C to +105°C (-40°F to +221°F)	PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP67, IP68, IP69K	MAXIMUM PANEL THICKNESS	6.0mm [.236]																						
CONTACT CARRIER MATERIAL	PVC																																														
CONTACT MATERIAL/PLATING	BRASS or COPPER/GOLD																																														
HOUSING MATERIAL/FINISH	STAINLESS STEEL/PASSIVATED																																														
GASKET MATERIAL	NITRILE (BUNA-N)																																														
RATED CURRENT [A]	25 A																																														
RATED VOLTAGE [V]	600 V																																														
CONDUCTOR INSULATION MATERIAL	PVC																																														
NUMBERS OF CONDUCTORS [AWG]	4x10 AWG																																														
TEMPERATURE RATING	-40°C to +105°C (-40°F to +221°F)																																														
PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP67, IP68, IP69K																																														
MAXIMUM PANEL THICKNESS	6.0mm [.236]																																														
<p>38.1 [1.50] Ø43.7 [1.72]</p>	<p>60.4 [2.38] 39.2 [1.54] 12.7 [0.50] 8.5 [0.33] REF. 3/4-14NPT LOCKNUT GASKET 10.0 [0.39] * METERS SEE NOTE 1</p>																																														
<table border="1"> <tr><th>CABLE LENGTH</th><th>TOLERANCE *</th></tr> <tr><td>ALL LENGTHS</td><td>+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER</td></tr> </table> <p>* UNLESS OTHERWISE SPECIFIED</p>		CABLE LENGTH	TOLERANCE *	ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER	<p>NOTES:</p> <p>1. "*" INDICATES LEAD LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.</p> <p>CAUTION: RISK OF ELECTRICAL SHOCK DO NOT DISCONNECT UNDER LOAD</p>																																									
CABLE LENGTH	TOLERANCE *																																														
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER																																														
<p>SOURCE DRAWING - FOR REFERENCE ONLY</p>																																															
<table border="1"> <tr> <td colspan="2">RELATED DOCUMENTS</td> <td>3RD ANGLE PROJECTION</td> <td colspan="2">THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.</td> </tr> <tr> <td colspan="2"> 1. 2. 3. 4. </td> <td> </td> <td colspan="2"></td> </tr> <tr> <td colspan="2">MATERIAL</td> <td rowspan="3">ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY</td> <td>DRFT</td> <td>RDS</td> </tr> <tr> <td colspan="2">SEE SPECIFICATIONS</td> <td>APVD</td> <td>SCALE 1=1.0</td> </tr> <tr> <td colspan="2">FINISH</td> <td colspan="2">UNIT OF MEASUREMENT</td> <td>MILLIMETER [INCH]</td> </tr> <tr> <td colspan="2">SEE SPECIFICATIONS</td> <td colspan="2">CONTACT TURCK FOR MORE INFORMATION</td> <td>DO NOT SCALE THIS DRAWING</td> </tr> <tr> <td colspan="2"></td> <td colspan="2"></td> <td>IDENTIFICATION NO. REV C</td> </tr> <tr> <td colspan="2"></td> <td colspan="2"></td> <td>FILE: 777020511</td> </tr> <tr> <td colspan="2"></td> <td colspan="2"></td> <td>SHEET 1 OF 1</td> </tr> </table>				RELATED DOCUMENTS		3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.		1. 2. 3. 4.					MATERIAL		ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY	DRFT	RDS	SEE SPECIFICATIONS		APVD	SCALE 1=1.0	FINISH		UNIT OF MEASUREMENT		MILLIMETER [INCH]	SEE SPECIFICATIONS		CONTACT TURCK FOR MORE INFORMATION		DO NOT SCALE THIS DRAWING					IDENTIFICATION NO. REV C					FILE: 777020511					SHEET 1 OF 1
RELATED DOCUMENTS		3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.																																												
1. 2. 3. 4.																																															
MATERIAL		ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY	DRFT	RDS																																											
SEE SPECIFICATIONS			APVD	SCALE 1=1.0																																											
FINISH			UNIT OF MEASUREMENT		MILLIMETER [INCH]																																										
SEE SPECIFICATIONS		CONTACT TURCK FOR MORE INFORMATION		DO NOT SCALE THIS DRAWING																																											
				IDENTIFICATION NO. REV C																																											
				FILE: 777020511																																											
				SHEET 1 OF 1																																											