

4 and 5-Wire M12 eurofast® Receptacles, Front Mount

- Female Receptacles
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection



Drawing Number	Part Number	Lead Specs.	Application	Pinout
<p>FK(N) ..</p>	FK 4.4-*	UL, CSA 4x22 AWG 105°C 250 V 4 A	Mates with 4-pin Cordsets	1. BN 2. WH 3. BU 4. BK
	FK 4.4-*/S613	UL, CSA 4x18 AWG 105°C 250 V 4 A	Mates with 4-pin Cordsets	1. BN 2. WH 3. BU 4. BK
	FK 4.4-*/S621	UL, CSA 4x18 AWG 105°C 250 V 4 A	Mates with 4-pin Cordsets	1. GY1 2. GY2 3. GY3 4. GY4
	FK 4.5-*	UL, CSA 5x22 AWG 105°C 250 V, 4 A	Mates with 5-pin Cordsets	1. BN 2. WH 3. BU 4. BK 5. GY
	FK 4.5-*/S627	UL, CSA 5x20 AWG 105°C 250 V, 4 A	Mates with 5-pin Cordsets	1. BN 2. WH 3. BU 4. BK 5. GY
	FK 4.5-*/S653	UL, CSA 4x22 AWG, Drain 105°C 250 V, 4 A 5.2 mm OD	Mates with 5-pin Cordsets, 4 conductors PVC foil shielded with drain wire to pin 5.	1. BN 2. WH 3. BU 4. BK 5. Drain
	FKN 5-*	UL, CSA 5x22 AWG, Drain 105°C 250 V, 4 A	See pinout	1. GN 2. WH 3. OG 4. BK 5. RD

See page D113 for dimensional drawings.

* Length in meters. Standard lead length is 0.5 Meters. Consult factory for other lengths. Standard housing material is nickel plated brass "FK."; "FKV.." indicates 316 stainless steel. To specify PVC jacketed cable, add "/S717" to the end of the part number.