


4 and 5-Wire M12 eurofast® Receptacles, Rear Mount with Leads

- Female Receptacles
- NEMA 1, 3, 4, 6P
- IEC IP 68 Protection



Drawing Number	Part Number	Lead Specs.	Application	Pinout
	FKFD 4.4-*	UL, CSA 4x22 AWG 105°C 250 V 4 A	Mates with 4-pin Cordsets	1. BN 2. WH 3. BU 4. BK
	FKFD 4.4-*/S621	UL, CSA 4x18 AWG 105°C 250 V 4 A	Mates with 4-pin cordsets	1. GY1 2. GY2 3. GY3 4. GY4
	FKFD 4.5-*	UL, CSA 5x22 AWG 105°C 250 V, 4 A	Mates with 5-pin Cordsets	1. BN 2. WH 3. BU 4. BK 5. GY
	FKFD 4.5-2/S653	UL, CSA 4x22 AWG, Drain 105°C 250 V, 4 A 5.2 mm OD	Mates with 5-pin Cordsets, 4 Conductors PVC Foil Shielded with Drain Wire to pin 5	1. BN 2. WH 3. BU 4. BK 5. Drain

Receptacles

See page D115 for dimensional drawings.

* Length in meters. Standard lead length is 0.5 meters. Consult factory for other lengths.
 Standard housing material is nickel plated brass "FKFD.."; "FKFDV.." indicates 316 stainless steel.
 To specify PVC jacketed cable, add "/S717" to the end of the part number.