

6 and 8-Wire Receptacles, Front Mount, 1/4-18 NPT Threads

- NEMA 1, 3, 4, 6P
- IEC IP68 Protection



Housing Style	Female Part Number	Male Part Number	Features	Pinout
<p>FK ..*/18.25</p> <p>Typical panel cutout is 14.3 mm.</p>	FK 4-6-*/18.25	FS 4-6-*/18.25	6x22 AWG, 105°C, 250 V, 2 A, Mates with 6-pin Cordsets	<p>Female</p> <p>Male</p>
	FK 6-*/18.25	FS 6-*/18.25	6x24 AWG, 105°C, 60 VAC/75 VDC, 2 A, Mates with 6-pin Cordsets	<p>Female</p> <p>Male</p>
	FK 8-*/18.25	FS 8-*/18.25	8x24 AWG, 105°C, 60 VAC/75 VDC, 2 A, Mates with 8-pin Cordsets	<p>Female</p>
	FK 8-*/18.25/S1505	FS 8-*/18.25/S1505	8x26 AWG, 105°C, 60 VAC/75 VDC, 2 A, Mates with 8-pin Cordsets	
<p>FS ..18.25</p> <p>Typical panel cutout is 14.3 mm.</p>	FK 8.6-*/18.25	FS 8.6-*/18.25	6x24 AWG, 105°C, 60 VAC/75 VDC, 2 A, Mates with 8-pin Cordsets	<p>Male</p>

* Length in meters. Standard lead length is 0.5 Meters. Consult factory for other lengths. Standard housing material is nickel plated brass "FS."; "FSV.." indicates stainless steel. To specify PVC jacketed cable, add "/S717" to the end of the part number.