




- NEMA 1, 3, 4, 6P
- IEC IP68 Protection



Housing Style	Female Part Number	Male Part Number	Features	Pinout
<p>FK../M20</p> <p>Typical panel cutout is 20.4 mm.</p>	FK 4.4-*/M20	FS 4.4-*/M20	4x22 AWG, 105°C, 250 V, 4 A, mates with 4-pin cordsets	<p>Female</p> <p>Male</p>
<p>FS../M20</p> <p>Typical panel cutout is 20.4 mm.</p>	FK 4.5-*/M20	FS 4.5-*/M20	5x22 AWG, 105°C, 250 V, 4 A, mates with 5-pin cordsets	<p>Female</p> <p>Male</p>
<p>FS../M20</p> <p>Typical panel cutout is 20.4 mm.</p>	FK 6-*/M20	FS 6-*/M20	6x24 AWG, 105°C, 60 VAC/75 VDC, 2 A, mates with 6-pin cordsets	<p>Female</p> <p>Male</p>

Receptacles

* Length in meters. Standard lead length is 0.5 Meters. Consult factory for other lengths.
Standard housing material is nickel plated brass "FS."; "FSV.." indicates stainless steel.
To specify PVC jacketed cable, add "/S717" to the end of the part number.