


8, 10 and 12-Wire Receptacles, Front Mount, M20 Threads

- NEMA 1, 3, 4, 6P
- IEC IP68 Protection
- 60 VAC/75 VDC, 2 A



Housing Style	Female Part Number	Male Part Number	Features	Pinout
<p>FK ../M20</p> <p>Typical panel cutout is 20.4 mm.</p>	FK 8-*/M20	FS 8-*/M20	8x24 AWG, 105°C, mates with 8-pin cordsets, UL Recognized, CSA Approved	<p>Female</p> <p>Male</p>
	FK 8.6-*/M20	FS 8.6-*/M20	6x24 AWG, 105°C, mates with 8-pin cordsets, UL Recognized, CSA Approved	<p>Female</p> <p>Male</p>
	FK 10-*/M20	FS 10-*/M20	10x24 AWG, 105°C, mates with 10-pin cordsets	<p>Female</p> <p>Male</p>
	FK 12-*/M20	FS 12-*/M20	12x24 AWG, 105°C, mates with 12-pin cordsets	<p>Female</p> <p>Male</p>

* Length in meters. Standard lead length is 0.5 Meters. Consult factory for other lengths. Standard housing material is nickel plated brass "FS."; "FSV.." indicates stainless steel. To specify PVC jacketed cable, add "/S717" to the end of the part number.