

5-Wire Receptacles, Front Mount, Reverse Key



- NEMA 1, 3, 4, 6P
- IEC IP68 Protection
- 250 V, 4 A



Housing Style	Female Part Number	Male Part Number	Features	Pinout
<p>FKW ..*</p> <p>Typical panel cutout is 15.2 mm.</p>	FKW 4.5-*	FSW 4.5-*	4x22, 1x20 AWG, 105°C, mates with 5-pin <u>Reverse Key Cordset</u>	1. BN 2. WH 3. BU 4. BK 5. GN/YE
<p>FSW ..</p> <p>Typical panel cutout is 15.2 mm.</p>	FKW 4.5-*/S653	FSW 4.5-*/S653	4x22 AWG, Drain 105°C, 5.1 mm OD, mates with 5-pin <u>Reverse Key Cordset</u> , 4 Conductors PVC Foil Shielded with Drain Wire to pin 5	<p>Female</p>
<p>FKW ..14.5</p> <p>Typical panel cutout is 21 mm.</p>	FKW 4.5-*/14.5	FSW 4.5-*/14.5	4x22, 1x20 AWG 105°C, mates with 5-pin <u>Reverse Key Cordset</u>	
<p>FSW ..14.5</p> <p>Typical panel cutout is 21 mm.</p>				<p>Male</p>
<p>FSW ..14.5/NPT</p> <p>Typical panel cutout is 22.5 mm.</p>	FKW 4.5*/14.5/NPT	FSW 4.5-*/14.5/NPT	4x22, 1x20 AWG 105°C, mates with 5-pin <u>Reverse Key Cordset</u>	

Receptacles

* Length in meters. Standard lead length is 0.5 Meters. Consult factory for other lengths. Standard housing material is nickel plated brass "FSW.."; "FSWV.." indicates stainless steel. To specify PVC jacketed cable, add "/S717" to the end of the part number.