

TURCK 1/2" microfast® Connectivity



2, 3 and 4-Wire Receptacles, Front Mount, 1/2-14 NPT Threads

- NEMA 1, 3, 4, 6P
- IEC IP67 Protection
- 250 V, 4 A



Housing Style	Female Part Number	Male Part Number	Features	Pinout
<p>FKB ...</p> <p>Typical panel cutout is 22.5 mm.</p>	FKB 2-*/14.5/NPT	FSB 2-*/14.5/NPT	2x18 AWG, 105°C	<p>Female</p> <p>Male</p>
<p>FSB ...</p> <p>Typical panel cutout is 22.5 mm.</p>	FKB 3-*/14.5/NPT	FSB 3-*/14.5/NPT	3x22 AWG, 105°C	<p>Female</p> <p>Male</p>
<p>FSB ...</p> <p>Typical panel cutout is 22.5 mm.</p>	FKB 4-*/14.5/NPT	FSB 4-*/14.5/NPT	4x22 AWG, 105°C	<p>Female</p> <p>Male</p>

microfast

* Length in meters. Standard lead length is 0.5 Meters. Consult factory for other lengths.
 Standard housing material is nickel plated brass."FSB."
 To specify PVC jacketed cable, add "/S717" to the end of the part number.