


TURCK 1/2" microfast® Connectivity



3 and 5-Wire Female Receptacles, Back Panel Mount, 11/16-24 Threads

- NEMA 1, 3, 4, 6P
- IEC IP67 Protection
- 250 V, 4 A



| Housing Style | Female Part Number | Features | Pinout |
|--|--------------------|-----------------|----------------------|
| <p>FKBP ...</p> <p>Recommended panel thickness is 5.1 mm and typical panel cutout is 17.5 x 3.2 x 1.6 mm.</p> | FKBP 3-* | 3x18 AWG, 105°C | <p>Female</p> |
| | FKBP 5-* | 5x18 AWG, 105°C | <p>Female</p> |

Standard housing material is nickel plated brass.

3, 4 and 5-Wire Shielded Bulkhead Feed-Thru Receptacles

- NEMA 1, 3, 4, 6P
- IEC IP67 Protection
- 250 V, 4 A



| Housing Style | Part Number | Features | Pinout |
|---|-------------|--------------|----------------------|
| <p>FKB FSB ..</p> <p>Recommended panel cutout thickness is 5.1 mm and typical panel cutout is 12.5 or 15.9 mm.</p> | FKB FSB 3 | 3-pin, 105°C | <p>Female</p> |
| | FKB FSB 4 | 4-pin, 105°C | <p>Female</p> |
| | FKB FSB 5 | 5-pin, 105°C | <p>Female</p> |

Standard housing material is nickel plated brass.