


## 2-6 Wire Extreme Duty, Armored Cordsets

- NEMA 1, 3, 4, 6P
- IEC IP67 Protection
- 300 V, 9 A (2-5-pin), 8 A (6-pin)



| Connector Style                   | Female Part Number | Male Part Number | Features                                                                                                                        | Pinout                                                                                                 |
|-----------------------------------|--------------------|------------------|---------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|
| <p>RKM ..A**</p> <p>RSM ..A**</p> | RKM 28A-*M         | RSM 28A-*M       | MC ITC/PLTC PVC Armor Yellow, 2x18 AWG, 105°C, 13.5 mm OD, Cable #RF51039-*M†, Armor Cable for Extreme Conditions, CSA Approved | <p>1. WH<br/>2. BK</p> <p><b>Female/Male</b></p>                                                       |
|                                   | RKM 38A-*M         | RSM 38A-*M       | MC ITC/PLTC PVC Armor Yellow, 3x18 AWG, 105°C, 13.5 mm OD, Cable #RF51040-*M†, Armor Cable for Extreme Conditions, CSA Approved | <p>1. GN<br/>2. BK<br/>3. WH</p> <p><b>Female</b></p> <p><b>Male</b></p>                               |
|                                   | RKM 48A-*M         | RSM 48A-*M       | MC ITC/PLTC PVC Armor Yellow, 4x18 AWG, 105°C, 13.5 mm OD, Cable #RF51041-*M†, Armor Cable for Extreme Conditions, CSA Approved | <p>1. BK<br/>2. WH<br/>3. RD<br/>4. GN</p> <p><b>Female</b></p> <p><b>Male</b></p>                     |
|                                   | RKM 58A-*M         | RSM 58A-*M       | MC PVC Armor Yellow, 5x18 AWG, 90°C, 14.9 mm OD, Cable #RF51042-*M†, Armor Cable for Extreme Conditions                         | <p>1. WH<br/>2. RD<br/>3. GN<br/>4. OG<br/>5. BK</p> <p><b>Female</b></p> <p><b>Male</b></p>           |
|                                   | RKM 68A-*M         | RSM 68A-*M       | MC PVC Armor Yellow, 6x18 AWG, 90°C, 14.9 mm OD, Cable #RF51043-*M†, Armor Cable for Extreme Conditions                         | <p>1. WH<br/>2. RD<br/>3. GN<br/>4. OG<br/>5. BK<br/>6. BU</p> <p><b>Female</b></p> <p><b>Male</b></p> |

\* Length in Meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.

\*\* Standard coupling nut material is nickel plated brass "RKM .."; "RKV .." indicates stainless steel.

† See Section N for **reelfast**® cable information.