


NETWORK WIRING

(M12x1) eurofast® Female Receptacles

- Mounted for Quick Connection to Enclosures
- Available for 1/2-14NPT, 1/2-14NPSM, 3/4-14NPT and M20 Threads



Housing	Female Part Number	Male Part Number	Application	Pinout
<p>FKV../14.5</p> <p>FSV../14.5</p>	FKV 49-*M/14.5	FSV 49-*M/14.5	Nickel plated CuZn or stainless steel, 250 V, 4 A, -40° to +105°C, 1/2-14NPT full length threads	<p>Female</p>
<p>FKV../14.75</p> <p>FSV../14.75</p>	FKV 49-*M/14.75	FSV 49-*M/14.75	Nickel plated CuZn or stainless steel, 250 V, 4 A, -40° to +105°C, 3/4-14NPT full length threads	
<p>FKV../M20</p> <p>24</p>	FKV 49-*M/M20	FSV 49-*M/M20	Nickel plated CuZn or stainless steel, 250 V, 4 A, -40° to +105°C, M20x1.5 Threads	<p>Male</p>

Standard cable length is 0.5 meters. Consult factory for other lengths.
 Standard housing material is stainless steel. "RKF .."; "RKFV .." indicates 316 nickel plated brass housing.