


DISTRIBUTED I/O SALES GUIDE

AS-interface®, eurofast® Male Receptacles



- Mounted for Quick Connection to Enclosures
- (M12x1) eurofast Connectors



Housing	Female Part Number	Male Part Number	Application	Pinout
<p>FK 25...14.5</p> <p>FS 25...14.5</p>	FK 25-*M/14.5	FS 25-*M/14.5	Nickel plated CuZn or stainless steel, 250 V, 4 A, -40° to +105°C, 1/2-14NPT full length threads	<p>Female</p>
<p>FK 25...14.75</p> <p>FS 25...14.75</p>	FK 25-*M/14.75	FS 25-*M/14.75	Nickel plated CuZn or stainless steel, 250 V, 4 A, -40° to +105°C, 3/4-14NPT full length threads	
<p>FK 25.../M20</p> <p>FS 25.../M20</p>	FK 25-*M/M20	FS 25-*M/M20	Nickel plated CuZn or stainless steel, 250 V, 4 A, -40° to +105°C, M20x1.5 threads	<p>1. BN 2. N/C 3. BU 4. N/C</p> <p>Male</p>

Standard cable length is 0.5 meters. Consult factory for other lengths.
Standard housing material is nickel plated brass. "RKF .."; "RKFV .." indicates 316 stainless steel housing.