





DISTRIBUTED I/O SALES GUIDE

PROFINET, (M12x1) *eurofast*®, RJ45, Cables and Extensions - Shielded Cable D-coded

		eurofast		
		RJ45 Plug	WRJ45 Plug	RJ45 IP67 Plug
		5  RJ45S	6  WRJ45ES	7  RJ45SMIP67
eurofast	Bare	RJ45S 42x-*M	WRJ45ES 42x-*M	RJ45SMIP67 42x-*M
	1  RSSD	RSSD RJ45S 42x-*M	RSSD WRJ45ES 42x-*M	RSSD RJ45SMIP67 42x-*M
	2  RKSD	RKSD RJ45S 42x-*M	RKSD WRJ45ES 42x-*M	RKSD RJ45SMIP67 42x-*M
	5  RJ45S	RJ45S RJ45S 42x-*M		RJ45S RJ45SMIP67 42x-*M
	6  WRJ45ES	WRJ45ES RJ45S 42x-*M	WRJ45ES WRJ45ES 42x-*M	WRJ45ES RJ45SMIP67 42x-*M
	7  RJ45SMIP67	RJ45SMIP67 RJ45S 42x-*M	RJ45SMIP67 WRJ45ES 42x-*M	RJ45SMIP67 RJ45SMIP67 42x-*M

See pages H35 - H36 for dimensional drawings.


* Indicates length in meters.

x Indicates cable type.

Standard cable lengths are 1, 2, 4, 6, 8, 10, 15, and in +5 meter increments from there. Consult factory for other lengths.

For stainless steel coupling nuts change part number RSSD ... RSSDV, FSSDED ... FSSDEDV.

For right angle RJ45, select WRJ45IS for internal tab or WRJ45ES for external tab.

eurofast	Pinouts	eurofast
Male 	1. Yellow (+ tx) 2. White (+rx) 3. Orange (-tx) 4. Blue (-rx)	Female 

RJ45 Pinout	RJ45 Plug	RJ45 (CR) Pinout
1. Yellow 2. Orange 3. White 4. N/C 5. N/C 6. Blue 7. N/C 8. N/C	Male  12345678	1. Yellow 2. Orange 3. White 4. N/C 5. N/C 6. Blue 7. N/C 8. N/C