


## DeviceNet™, (M12x1) eurofast® Male Receptacles

- Provides Quick Connection to Field Devices
- Available for 1/2-14NPT, 1/2-14NPSM, 3/4-14NPT and M20 Threads



Housing Style	Female Part Number	Male Part Number	Features	Pinout
<p><b>FK 57../14.5</b></p> <p><b>FS 57../14.5</b></p>	FK 57-*M/14.5	FS 57-*M/14.5	Nickel plated CuZn or stainless steel, 250 V, 4 A, -40° to +105°C, 1/2-14NPT full length threads	<p><b>Female</b></p>
<p><b>FK 57../14.75</b></p> <p><b>FS 57../14.75</b></p>	FK 57-*M/14.75	FS 57-*M/14.75		
<p><b>FK 57.../M20</b></p> <p><b>FS 57.../M20</b></p>	FK 57-*M/M20	FS 57-*M/M20	Nickel plated CuZn or stainless steel, 250 V, 4 A, -40° to +105°C, M20x1.5 threads	<p><b>Male</b></p>

\* Length in meters.  
 Standard cable length is 0.5 meters. Consult factory for other lengths.  
 Standard housing material is nickel plated brass. "RKF .."; "RKfV .." indicates 316 stainless steel housing.