

FEMALE END VIEW

1 = SHIELD
2 = + VOLTAGE
3 = - VOLTAGE
4 = CAN_H
5 = CAN_L

DeviceNet™

BOARD LAYOUT SCALE 2=1

PA6 PIN SUPPORT AND PRINTED CIRCUIT

SPECIFICATIONS

CONTACT CARRIER MATERIAL/COLOR	NYLON OR TPU/BLEU-GRAY
CONTACT MATERIAL/PLATING	BRASS/GOLD
RATED CURRENT [A]	4.0 A
RATED VOLTAGE [V]	250 V
HOUSING, LOCKNUT MATERIAL/PLATING	BRASS/NICKEL
NUMBER OF CONDUCTORS [AWG]	PRINTED CIRCUIT PINS
TEMPERATURE RATING	-40°C to +105°C (-40°F to +221°F)
PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP68

LOCKNUT

M12x1 PG 9

O-RING GROOVE

O-RING GROOVE

NOTES:

1. "/S3004" DESIGNATES BULK PACKED, NO LABEL, NO BAG.

SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS	3RD ANGLE PROJECTION	THIS DRAWING IS PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.	TURCK INC High Technology Sensors and Automation Controls 3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax turck.com	
1. 2. 3. 4.		DRFT RDS	DATE 04/16/08	DESCRIPTION
MATERIAL	SEE SPECIFICATIONS	DSGN	SCALE 1=.8	FKFD 57-PCB/S3004
FINISH	CONTACT TURCK FOR MORE INFORMATION	UNIT OF MEASUREMENT		IDENTIFICATION NO.
		MILLIMETER [INCH]		U2-13603
		DO NOT SCALE THIS DRAWING		REV C
C	DRAWING PROCESSED AS PART OF ECO 33971	CBM	04/07/11	33971
REV	DESCRIPTION	BY	DATE	ECO NO.